

Mill Test Certificate

Bri-Steel Manufacturing Inc.

2125-64 Avenue, Edmonton, AB Canada T6P 1Z4 Fax: 001 (780) 469-6986 Tel: 001 (780) 469-6603 www.brichemsteel.com

Product: Seamless Carbon Steel Pipe

Product Heat Number: BSM-0576

Product Size:

NPS 16 SCH 80*

Production Date:

November 27, 2012

Production Method: Hot Expansion

Product Heat Treatment: As-rolled

Product Standards: ASME B36.10-2004, ASTM/ASME A/SA106-2011 Grade B NDE, A/SA53-2012 Grade B Type S, NACE MR0175-2009, MR0103-2010

Product Markings: .BRI-STEEL MFG ASTM/ASME A/SA106 GR B/C A/SA53 GR B NPS 16 SCH 80 HEAT BSM-0576 (PIPE # LENGTH MASS) 164.81b/ft NDE SMLS NACE MR0175 2012/11 MADE IN CANADA.

| BSM-0576 | Heat | | |
|-----------|-----------|-----------|---------------------|
| Heat | Test Type | | |
| 16 | NPS | | P |
| SCH 80* | Thickness | Wall | Product Details |
| 27 | Pieces | | S |
| DRL | Length | | |
| 164.80 | lb/ft | Mass | |
| <5 | μR/hr | Geiger | |
| <20 | Gauss | Res.Mag. | |
| Pass | Insp. | Visual | |
| Pass | OD | | Non-I |
| Pass | WT | TU | Destructive Testing |
| Pass | ASTM E213 | UT | |
| Pass | ASTM E309 | ET | |
| 1 | | HydroTest | |
| Plain End | Condition | End | |

| BSN | | _ | |
|----------------------------|-------------------------------------|--------------------|-------------------------|
| BSM-0576 | | Heat | |
| Vacuum Degas; Fully Killed | Blast Furnace; EAF; Ladle Refining; | Steelmaking Method | |
| Product | Heat | Analysis | |
| 0.19 | 0.20 | С | |
| 0.88 | 0.89 | M | |
| 0.004 | 0.006 | Р | |
| 0.004 0.005 | 0.007 | S | Chemica |
| 0.22 | 0.25 | Si | Chemical Analysis (wt%) |
| 0.06 | 0.06 | Çr | (wt%) |
| 0.06 | 0.06 | C. | |
| 0.05 | 0.06 | Mo | |
| 0.03 | 0.03 | <u>Z</u> | |
| 0.002 | ı | < | |
| 0.001 | | Ті | |
| 0.001 | - | Nb | |
| 0.0003 | 0.0006 | В | |
| 0.37 | • | (IIW) | |
| 0.37 | 1 | CE (CSA) | |

| | BSM-0576 Heat | Heat | | |
|---------------------------|-------------------------|-----------------|----------------|-----------------------|
| | Heat | Test Type | | |
| | Ferrite & Pearlite | Microstructure | | |
| | 74 | HRBW | Hardness | |
| | Pass | Flattening Test | | Mechar |
| Longitudinal; 19.1mm x WT | Transverse; 19.1mm x WT | 50mm GL | Tension Test | Mechanical Properties |
| 42,500 | 44,800 | psi | Yield (Rt0.5) | |
| 42,400 | 44,700 | psi | Yield (Rp0.2) | |
| 70,000 | 73,000 | psi | Tensile (Rm) | |
| 0.61 | 0.61 | (Rt0.5/Rm) | 1/4 | |
| 47 | 41 | % | Elongation (A) | |

Additional Details:

Inc. in accordance with ASTM/ASME A/SA106-2011, A/SA53-2012 and the purchase order requirements, and that the ✓ We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing

results meet the corresponding requirements.

Service, and NACE MR0103-2010 Section 2.1. This pipe product meets the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3 Sour

No weld repairs have been performed on this product.

This product has not come into contact with mercury during the Bri-Steel Manufacturing processes

√ This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1.

*Note that these pipes were downgraded from NPS 16 SCH 100.

Mill Test Certificate approved by:

20122010

Manager of Quality and R&D Kenton Dechant, P.Eng.