

Mill Test Certificate

Bri-Steel Manufacturing Inc.

2125-64 Avenue, Edmonton, AB Canada T6P 1Z4 Fax: 001 (780) 469-6986 Tel: 001 (780) 469-6603 www.brichemsteel.com

Product: Seamless Carbon Steel Pipe

Product Heat Number: BSM-0582

Product Size:

December 3, 2012

Production Method:

NPS 20 TRUE80

Production Date:

Hot Expansion Product Heat Treatment: As-rolled

Product Standards: ASME B36.10-2004, ASTM/ASME A/SA106-2011 Grade B NDE, A/SA53-2012 Grade B Type S, NACE MR0175-2009, MR0103-2010

Product Markings: .BRI-STEEL MFG ASTM/ASME A/SA106 GR B/C A/SA53 GR B NPS 20 TRUE80 HEAT BSM-0582 (PIPE # LENGTH MASS) 208.91b/ft NDE SMLS NACE MR0175 2012/12 MADE IN CANADA.

| BSM-0582 | Heat | | |
|---------------|-----------|-----------|----------------|
| Heat | Test Type | | |
| 20 | NPS | | F |
| TRUE80 | Thickness | Wall | roduct Detail: |
| ш | Pieces | | S |
| DRL | Length | | |
| 208.90 | lb/ft | Mass | |
| < 5 | μR/hr | Geiger | |
| <20 | Gauss | Res.Mag. | |
| Pass | Insp. | Visual | |
| Pass | OD | | Non-D |
| Pass | WT | TU | estructive . |
| Pass | ASTM E213 | TU | esting |
| Pass | ASTM E309 | ET | |
| 1 | | HydroTest | |
| Plain End | Condition | End | |

| | BSM-0582 | | | | | |
|----------------------------|-------------------------------------|-------------------------|--------------------|-----|--------|-------------------------|
| Vacuum Degas; Fully Killed | Blast Furnace; EAF; Ladle Refining; | Occumental State Colors | Steelmaking Method | | | |
| Product | Heat | Tildiyaia | Analysis | | | |
| 0.21 | 0.20 | (| 7 | | | |
| 0.94 | 0.94 | 11141 | 2 | 8 | VDW07- | |
| 0.013 | 0.013 | - | 0 | | | |
| 0.011 | 0.010 | C | 0 | | | Chemical Analysis (wt%) |
| 0.21 | 0.22 | 2 | Ω | | | Analysis |
| 0.05 | 0.05 | 2 | , | | | (wt%) |
| 0.07 | 0.07 | C | ? | | | |
| 0.03 | 0.03 | MC | 2 | | | |
| 0.04 | 0.05 | N | - | | | |
| 0.003 | 0.000 | < | | | | |
| 0.001 | 0.001 | = | ! | | | |
| 0.001 | 0.000 | ND | • | | | |
| 0.0003 | 0.0003 | 0 | , | | | |
| 0.39 | r | (IIVV) | (1114) | CF. | 2 | |
| 0.40 | ı | (CSA) | 1000 | CF | 3 | |

| | BSM-0582 Heat | Heat | | |
|---------------------------|-------------------------|-----------------|----------------|-----------------------|
| | Heat | Test Type | | |
| | Ferrite & Pearlite | Microstructure | | |
| | 76 | HRBW | Hardness | |
| | Pass | Flattening Test | | Mechar |
| Longitudinal; 38.1mm x WT | Transverse; 38.1mm x WT | 50mm GL | Tension Test | Mechanical Properties |
| 43,800 | 54,000 | psi | Yield (Rt0.5) | |
| 42,900 | 52,000 | psi | Yield (Rp0.2) | |
| 71,000 | 72,000 | psi | Tensile (Rm) | |
| 0.62 | 0.75 | (Rt0.5/Rm) | Υ/Τ | |
| 51 | 49 | % | Elongation (A) | |

Additional Details:

results meet the corresponding requirements. Inc. in accordance with ASTM/ASME A/SA106-2011, A/SA53-2012 and the purchase order requirements, and that the ✓ We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing

Service, and NACE MR0103-2010 Section 2.1. This pipe product meets the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3 Sour

No weld repairs have been performed on this product.

√ This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1. \checkmark This product has not come into contact with mercury during the Bri-Steel Manufacturing processes

Mill Test Certificate approved by:

Manager of Quality and R&D Kenton Dechant, P.Eng.

2012 Dec 2/