

Mill Test Certificate

Bri-Steel Manufacturing Inc.

2125-64 Avenue, Edmonton, AB Canada T6P 1Z4 Fax: 001 (780) 469-6986 Tel: 001 (780) 469-6603

www.brichemsteel.com

Product: Seamless Carbon Steel Pipe Product Heat Number:

Production Method:

BSM-0600

Product Size:

NPS 20 TRUE80

Production Date: December 11, 2012

Hot Expansion Product Heat Treatment:

As-rolled

Product Standards: ASME B36.10-2004, ASTM/ASME A/SA106-2011 Grade B NDE, A/SA53-2012 Grade B Type S, NACE MR0175-2009, MR0103-2010

Product Markings: .BRI-STEEL MFG ASTM/ASME A/SA106 GR B A/SA53 GR B NPS 20 TRUE80 HEAT BSM-0600 (PIPE # LENGTH MASS) 208.9lb/ft NDE SMLS NACE MR0175 2012/12 MADE IN CANADA.

1	_	_		_
	BSM-0600	Heat		
	Heat	Test Type		
	20	NPS		F
	TRUE80	Thickness	Wall	Product Details
	8	Pieces		S
	DRL	Length		
	208.90	lb/ft	Mass	
	S	μR/hr	Geiger	
	<20	Gauss	Res.Mag.	
	Pass	Insp.	Visual	
	Pass	OD		Non-D
	Pass	ΨT	TU	Non-Destructive Testing
	Pass	ASTM E213	UT	Testing Testing
2	Pass	ASTM E309	ET	
	*	***	HydroTest	
	Plain End	Condition	End	
		Heat 20 TRUE80 8 DRL 208.90 <5 <20 Pass Pass Pass Pass *	Test Type NPS Thickness Pieces Length lb/ft μR/hr Gauss Insp. OD WT ASTM E213 ASTM E309 Heat 20 TRUE80 8 DRL 208.90 <5 <20 Pass Pass Pass Pass *	Wall Wall Mass Geiger Res.Mag. Visual UT UT ET HydroTest Type NPS Thickness Pieces Length lb/ft μR/hr Gauss Insp. OD WT ASTM E213 ASTM E309 Heat 20 TRUE80 8 DRL 208.90 <5 <20 Pass Pass Pass Pass Pass *

	RSM-0	Heat		
-	BSM-0600			
Vacuum Degas; Fully Killed	Blast Furnace; EAF; Ladle Refining;	Steelmaking Method		
Product	Heat	Analysis		
0.19	0.20	0		
0.90	0.90	Mn		
0.90 0.012	0.012	P		
0.005 0.27	0.003	s		Chemical Analysis (wt%)
0.27	0.28	Si		Analysis
0.03	0.04	Ç		(wt%)
0.05	0.04	Cu		
0.01	0.01	Мо		
0.02	0.02	Z.		
0.003	0.003	<		
0.003	0.003	1		
0.001	0.001	Nb		
0.0001	0.0003	В		
0.35	1	(WII)	CE	
0.36	ı	(CSA)	CE	

	BSM-0600	Heat		
	Heat	Test Type		
	Ferrite & Pearlite	Microstructure		
	76	HRBW	Hardness	
	Pass	Flattening Test		Mechar
Longitudinal; 38.1mm x WT	Transverse; 38.1mm x WT	50mm GL	Tension Test	Mechanical Properties
46,700	48,700	psi	Yield (Rt0.5)	
46,100	44,800	psi	Yield (Rp0.2)	
69,000	69,500	psi	Tensile (Rm)	
0.68	0.70	(Rt0.5/Rm)	T/Y	
59	59	%	Elongation (A)	

Additional Details:

Inc. in accordance with ASTM/ASME A/SA106-2011, A/SA53-2012 and the purchase order requirements, and that the results meet the corresponding requirements. ✓ We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing

Service, and NACE MR0103-2010 Section 2.1. This pipe product meets the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3 Sour

No weld repairs have been performed on this product.

This product has not come into contact with mercury during the Bri-Steel Manufacturing processes

√ This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1.

*Note that this product was hydrotested to 1000 psi for 5 seconds

Mill Test Certificate approved by:

Manager of Quality and R&D Kenton Dechant, P.Eng. 2013 Jan