

Mill Test Certificate

2125-64 Avenue, Edmonton, AB Canada T6P 1Z4 Bri-Steel Manufacturing Inc.

Fax: 001 (780) 469-6986 Tel: 001 (780) 469-6603

www.brichemsteel.com

Product: Seamless Carbon Steel Pipe

Product Heat Number: BSM-0607

Product Size:

NPS 20 SCH 100

Production Date:

December 13, 2012

Production Method: Hot Expansion

Product Heat Treatment: As-rolled

Product Standards: ASME B36.10-2004, ASTM/ASME A/SA106-2011 Grade B NDE, A/SA53-2012 Grade B Type S, NACE MR0175-2009, MR0103-2010

Product Markings: .BRI-STEEL MFG ASTM/ASME A/SA106 GR B A/SA53 GR B NPS 20 SCH 100 HEAT BSM-0607 (PIPE # LENGTH MASS) 256.1lb/ft NDE SMLS NACE MR0175 2012/12 MADE IN CANADA.

BSM-0607	Heat		
)7 Heat	Test Type		
20	NPS		
SCH 100	Thickness	Wall	Product Detail
6	Pieces		ils
DRL	Length		
256.10	lb/ft	Mass	
<5	μR/hr	Geiger	
<20	Gauss	Res.Mag.	
Pass	Insp.	Visual	250
Pass	OD		Non-
Pass	TW	TU	Destructive
Pass	ASTM E213	TU	Testing
Pass	3 ASTM E309	ET	
*	_	HydroTest	
Plain End	Condition	End	

0.14	RSM-0607	Heat		
000,		at		
Vacuum Degas; Fully Killed	Blast Furnace; EAF; Ladle Refining;	Steelmaking Method		
Product	Heat	Analysis		
0.19	0.19	C		
0.95	0.96	Mn		
0.015	0.014	Р		
0.005	0.004	S		Chemical Analysis (wt%)
0.27	0.30	Si		Analysis
0.04	0.06	Cr		(wt%)
0.09	0.08	Си		
0.01	0.01	Мо		
0.04	0.03	Z.		
0.003	0.004	<		
0.002	0.003	Ħ		
0.001	0.001	Nb		
0.0002	0.0001	В		
0.37	ı	(IIW)	CE	
0.37	ı	(CSA)	CE	

	BSN	Ţ		
	BSM-0607	Heat		
	Heat	Test Type		
	Ferrite & Pearlite	Microstructure		
	72	HRBW	Hardness	
	Pass	Flattening Test		Mechan
Longitudinal; 19.1mm x WT	Transverse; 19.1mm x WT	50mm GL	Tension Test	Mechanical Properties
39,100	42,400	psi	Yield (Rt0.5)	
38,600	44,500	psi	Yield (Rp0.2)	
67,500	69,500	psi	Tensile (Rm)	
0.58	0.61	(Rt0.5/Rm)	Τ/Υ	
54	52	%	Elongation (A)	

Additional Details:

results meet the corresponding requirements. Inc. in accordance with ASTM/ASME A/SA106-2011, A/SA53-2012 and the purchase order requirements, and that the ✓ We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing

Service, and NACE MR0103-2010 Section 2.1. This pipe product meets the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3 Sour

No weld repairs have been performed on this product.

 \checkmark This product has not come into contact with mercury during the Bri-Steel Manufacturing processes

√ This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1.

*Note that this product was hydrotested to 1000 psi for 5 seconds.

Mill Test Certificate approved by:

2013 Jan 7

Manager of Quality and R&D Kenton Dechant, P.Eng.

Cert # 240



Mill Test Certificate

2125-64 Avenue, Edmonton, AB Canada T6P 1Z4 **Bri-Steel Manufacturing Inc.**

Fax: 001 (780) 469-6986 Tel: 001 (780) 469-6603 www.brichemsteel.com

Product: Seamless Carbon Steel Pipe

Production Method:

Product Heat Number:

BSM-0607

Product Size: NPS 20 SCH 120

Production Date: December 13, 2012

Hot Expansion Product Heat Treatment: As-rolled

Product Standards: ASME B36.10-2004, ASTM/ASME A/SA106-2011 Grade B NDE, A/SA53-2012 Grade B Type S, NACE MR0175-2009, MR0103-2010

.BRI-STEEL MFG ASTM/ASME A/SA106 GR B A/SA53 GR B NPS 20 SCH 120 HEAT BSM-0607 (PIPE # LENGTH MASS) 296.41b/ft NDE SMLS NACE MR0175 2012/12 MADE IN CANADA.

Product Markings:

BSM-0607	Heat		
Heat	Test Type		
20	NPS		P
SCH 120	Thickness	Wall	Product Detail
6	Pieces		s
DRL	Length		
296.40	lb/ft	Mass	
<5	μR/hr	Geiger	
<20	Gauss	Res.Mag.	
Pass	Insp.	Visual	
Pass	OD		Non-D
Pass	TW	TU	estructive T
Pass	ASTM E213	TU	esting
Pass	// E213 ASTM E309	ET	
*		HydroTest	
Plain End	Condition	End	

0.00	RSM-0607	Heat		
Vacuum Degas; Fully Killed	Blast Furnace; EAF; Ladle Refining;	Steelmaking Method		
Product 0.19 0.95 0.015 0.005 0.27 0.04	Heat	Analysis		
0.19	0.19	С		
0.95	0.96	Mn		
0.015	0.014	P		
0.005	0.96 0.014 0.004 0.30	S		Chemica
0.27	0.30	Si		Chemical Analysis (wt%)
0.04	0.06	Cr		(wt%)
0.09	0.08	Cu		
0.01	0.01	Mo		
0.04	0.03	Z.		
0.003	0.004	<		23
0.002	0.003	Ti		
0.001	0.001	Nb		
0.0002	0.0001	В		
0.37	•	(IIW)	CE	
0.37		(CSA)	CE	

	BSM-0607 Heat	Heat		
	Heat	Test Type		
	Ferrite & Pearlite	Microstructure		
	72	HRBW	Hardness	
	Pass	Flattening Test		Mechar
Longitudinal; 19.1mm x WT	Transverse; 19.1mm x WT	50mm GL	Tension Test	Mechanical Properties
39,100	42,400	psi	Yield (Rt0.5)	
38,600	44,500	psi	Yield (Rp0.2)	
67,500	69,500	psi	Tensile (Rm)	
0.58	0.61	(Rt0.5/Rm)	T/Y	
54	52	%	Elongation (A)	

Additional Details:

results meet the corresponding requirements. Inc. in accordance with ASTM/ASME A/SA106-2011, A/SA53-2012 and the purchase order requirements, and that the ✓ We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing

Service, and NACE MR0103-2010 Section 2.1. This pipe product meets the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3 Sour

No weld repairs have been performed on this product.

This product has not come into contact with mercury during the Bri-Steel Manufacturing processes

This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1.

*Note that this product was hydrotested to 1000 psi for 5 seconds

Mill Test Certificate approved by:

Kenton Dechant, P.Eng.

Manager of Quality and R&D

今の女かり