

## Mill Test Certificate

Bri-Steel Manufacturing Inc.

2125-64 Avenue, Edmonton, AB Canada T6P 1Z4 Fax: 001 (780) 469-6986 Tel: 001 (780) 469-6603

www.brichemsteel.com

Product: Seamless Carbon Steel Pipe

**Product Heat Number:** BSM-0615

Product Size:

NPS 20 SCH 160

Production Date:

December 19, 2012

Production Method: Hot Expansion

Product Markings:

Product Standards:

Product Heat Treatment: As-rolled

ASME B36.10-2004, ASTM/ASME A/SA106-2011 Grade B/C NDE, A/SA53-2012 Grade B Type S, NACE MR0175-2009, MR0103-2010

BSM-0615 Heat	Heat Test Type		
20	NPS		
SCH 160	Thickness	Wall	Product Detail
0	Pieces		ils
DRL	Length		
379.00	lb/ft	Mass	
<5	μR/hr	Geiger	
<20	Gauss	Res.Mag.	
Pass	insp.	Visual	
Pass	OD		Non-D
Pass	WT	TU	estructive T
Pass	ASTM E213	TU	esting
Pass	ASTM E309	ET	
*		HydroTest	
Plain End	Condition	End	

Plain End

.BRI-STEEL MFG ASTM/ASME A/SA106 GR B/C A/SA53 GR B NPS 20 SCH 160 HEAT BSM-0615 (PIPE # LENGTH MASS) 3791b/ft NDE SMLS NACE MR0175 2012/12 MADE IN CANADA.

						Chemical	Chemical Analysis (wt%)	(wt%)									
																CE	Œ
Heat	Steelmaking Method	Analysis	С	Mn	P	S	Si	Ç	Cu	Mo	Ζ.	<	∄	S	В	(E)	(CSA)
RSM-0615	Blast Furnace; EAF; Ladle Refining;	Heat	0.20	0.88	0.015	0.006	0.28	0.05	0.06	0.01	0.02	0.003	0.002	0.001	0.0002	1	ı
0	Vacuum Degas; Fully Killed	Product	0.20	0.93	0.013	0.005	0.27	0.04	0.05	0.01	0.02	0.003	0.003	0.001	0.0002	0.37	0.38

	BSM-0615	Heat		
	5 Heat	Test Type		
	Ferrite & Pearlite	Microstructure		
	74	HRBW	Hardness	
	Pass	Flattening Test		Mechar
Longitudinal; 38.1mm x WT	Transverse; 38.1mm x WT	50mm GL	Tension Test	Mechanical Properties
45,500	48,700	psi	Yield (Rt0.5)	
45,900	50,000	psi	Yield (Rp0.2)	
69,000	71,000	psi	Tensile (Rm)	
0.66	0.69	(Rt0.5/Rm)	Τ/Υ	
53	46	%	Elongation (A)	

Additional Details:

Inc. in accordance with ASTM/ASME A/SA106-2011, A/SA53-2012 and the purchase order requirements, and that the results meet the corresponding requirements. ✓ We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing

Service, and NACE MR0103-2010 Section 2.1. This pipe product meets the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3 Sour

No weld repairs have been performed on this product.

✓ This product has not come into contact with mercury during the Bri-Steel Manufacturing processes

\*Note that this product was hydrotested to 1000 psi for 5 seconds This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1.

Mill Test Certificate approved by:

Manager of Quality and R&D Kenton Dechant, P.Eng. 2013 Jan 18