## Bri-Steel Manufacturing Inc.

2125-64 Avenue, Edmonton, AB Canada T6P 1Z4 Fax: 001 (780) 469-6986 Tel: 001 (780) 469-6603 www.brichemsteel.com

## Mill Test Certificate

Product: Seamless Carbon Steel Pipe Product Heat Number: BSM-0616 Product Size: NPS 20 SCH 140 Production Date: December 19, 2012

Production Method: **Hot Expansion** Product Heat Treatment: As-rolled

Product Standards: ASME B36.10-2004, ASTM/ASME A/SA106-2011 Grade B/C NDE, A/SA53-2012 Grade B Type S, NACE MR0175-2009, MR0103-2010

Product Markings: .BRI-STEEL MFG ASTM/ASME A/SA106 GR B/C A/SA53 GR B NPS 20 SCH 140 HEAT BSM-0616 (PIPE # LENGTH MASS) 341.11b/ft NDE SMLS NACE MR0175 2012/12 MADE IN CANADA.

|  | BSM-0616  | Heat      |           |                 |
|--|-----------|-----------|-----------|-----------------|
|  | Heat      | Test Type |           |                 |
|  | 20        | NPS       |           |                 |
|  | SCH 140   | Thickness | Wall      | Product Details |
|  | 6         | Pieces    |           | ls              |
|  | DRL       | Length    | 201       |                 |
|  | 341.10    | lb/ft     | Mass      |                 |
|  | Ĝ         | μR/hr     | Geiger    |                 |
|  | <20       | Gauss     | Res.Mag.  |                 |
|  | Pass      | Insp.     | Visual    |                 |
|  | Pass      | OD        |           | Non-E           |
| 200  | Pass      | WT        | S         | Destructive T   |
|  | Pass      | ASTM E213 | TU        | ve Testing      |
| The second secon | Pass      | ASTM E309 | ET        |                 |
|  | *         |           | HydroTest |                 |
|  | Plain End | Condition | End       |                 |

|          |                                     |          |      |      |       | Chemical A | Analysis (wt%) | (wt%) |      |      |            |       |       |       |        |       |       |
|----------|-------------------------------------|----------|------|------|-------|------------|----------------|-------|------|------|------------|-------|-------|-------|--------|-------|-------|
|          |                                     |          |      |      |       |            |                |       |      |      |            |       |       |       |        | Œ     | CE    |
| Heat     | Steelmaking Method                  | Analysis | C    | Mn   | P     | S          | Si             | Cr    | Cu   | Mo   | <u>Z</u> . | <     | =!    | В     | В      | (IIV) | (CSA) |
| BSM-0616 | Blast Furnace; EAF; Ladle Refining; | Heat     | 0.22 | 0.89 | 0.013 | 0.005      | 0.27           | 0.04  | 0.05 | 0.01 | 0.02       | 0.003 | 0.002 | 0.001 | 0.0002 | ı     | 1     |
|          | Vacuum Degas; Fully Killed          | Product  | 0.21 | 0.92 | 0.012 | 0.005      | 0.28           | 0.04  | 0.06 | 0.01 | 0.02       | 0.003 | 0.003 | 0.001 | 0.0002 | 0.38  | 0.39  |
|          |                                     |          |      |      |       |            |                |       |      |      |            |       |       |       |        |       |       |

|                           | BSM-0616                | Heat            |                |                       |
|---------------------------|-------------------------|-----------------|----------------|-----------------------|
|                           | Г                       | -               |                |                       |
|                           | Heat                    | Test Type       |                |                       |
|                           | Ferrite & Pearlite      | Microstructure  |                |                       |
|                           | 74                      | HRBW            | Hardness       |                       |
|                           | Pass                    | Flattening Test |                | Mechar                |
| Longitudinal; 19.1mm x WT | Transverse; 19.1mm x WT | 50mm GL         | Tension Test   | Mechanical Properties |
| 43,900                    | 53,500                  | psi             | Yield (Rt0.5)  |                       |
| 43,900                    | 51,000                  | psi             | Yield (Rp0.2)  |                       |
| 71,500                    | 71,500                  | psi             | Tensile (Rm)   | 1                     |
| 0.61                      | 0.75                    | (Rt0.5/Rm)      | T/Y            |                       |
| 51                        | 46                      | %               | Elongation (A) |                       |

Additional Details:

results meet the corresponding requirements. Inc. in accordance with ASTM/ASME A/SA106-2011, A/SA53-2012 and the purchase order requirements, and that the ✓ We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing

Service, and NACE MR0103-2010 Section 2.1. This pipe product meets the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3 Sour

No weld repairs have been performed on this product.

 $\checkmark$  This product has not come into contact with mercury during the Bri-Steel Manufacturing processes

√ This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1.

\*Note that this product was hydrotested to 1000 psi for 5 seconds.

Mill Test Certificate approved by:

Manager of Quality and R&D Kenton Dechant, P.Eng.

2013 Jan 8