

## Mill Test Certificate

2125-64 Avenue, Edmonton, AB Canada T6P 1Z4 Bri-Steel Manufacturing Inc.

Fax: 001 (780) 469-6986 www.brichemsteel.com Tel: 001 (780) 469-6603

Product: Seamless Carbon Steel Pipe

Product Heat Number: BSM-0643

Product Size:

NPS 24 TRUE80

Production Date:

Production Method: Hot Expansion

Product Heat Treatment: As-rolled

January 9, 2013

Product Standards: ASME B36.10-2004, ASTM/ASME A/SA106-2011 Grade B NDE, A/SA53-2012 Grade B Type S, NACE MR0175-2009, MR0103-2010

Product Markings: .BRI-STEEL MFG ASTM/ASME A/SA106 GR B A/SA53 GR B NPS 24 TRUE80 HEAT BSM-0643 (PIPE # LENGTH MASS) 296.4lb/ft NDE SMLS NACE MR0175 2013/01 MADE IN CANADA.

BSM-0643	Heat		
Heat	Test Type		
24	NPS		
TRUE80	Thickness	Wall	Product Details
5	Pieces		S
DRL	Length		
296.40	lb/ft	Mass	
Ġ	μR/hr	Geiger	
<20	Gauss	Res.Mag.	
Pass	Insp.	Visual	
Pass	OD		Non-I
Pass	TW	TU	estructive)
Pass	ASTM E213	TU	Testing
Pass	ASTM E309	ET	
*	3	HydroTest	
Plain End	Condition	End	

	BSM-0643	Heat		
Vacuum Degas; Fully Killed	.3 Blast Furnace; EAF; Ladle Refining;	Steelmaking Method		
Product	Heat	Analysis		
0.14	0.13	0		
1.01	0.98	Mn		
0.017	0.016	P		
0.017   0.005	0.002	S		Chemica
0.26	0.26	Si		Chemical Analysis (wt%)
0.06	0.06	Cr		(wt%)
0.07	0.06	Cu		
0.02	0.01	Mo		
0.03	0.02	Z.		
0.004	0.004	<		
0.003	0.002	Ti		
0.001	0.001	Nb		
0.0001	0.0001	В		
0.33	1	(IIW)	Œ	
0.31		(CSA)	CE	

	BSM-0643	Heat		
	BSM-0643 Heat	Test Type		
	Ferrite & Pearlite	Microstructure		
	73	HRBW	Hardness	
	Pass	Flattening Test		Mechar
Longitudinal; 38.1mm x WT	Transverse; 38.1mm x WT	50mm GL	Tension Test	Mechanical Properties
44,400	50,000	psi	Yield (Rt0.5)	
44,500	49,100	psi	Yield (Rp0.2)	
64,000	66,000	psi	Tensile (Rm)	
0.69	0.76	(Rt0.5/Rm)	Υ/Τ	
64	63	%	Elongation (A)	

Additional Details:

results meet the corresponding requirements Inc. in accordance with ASTM/ASME A/SA106-2011, A/SA53-2012 and the purchase order requirements, and that the ✓ We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing

Service, and NACE MR0103-2010 Section 2.1. This pipe product meets the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3 Sour

No weld repairs have been performed on this product.

This product has not come into contact with mercury during the Bri-Steel Manufacturing processes

√ This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1.

\*Note that this product was hydrotested to 1000 psi for 5 seconds.

Mill Test Certificate approved by:

2013 Jan 18

Manager of Quality and R&D Kenton Dechant, P.Eng.



## Mill Test Certificate

2125-64 Avenue, Edmonton, AB Canada T6P 1Z4 **Bri-Steel Manufacturing Inc.** 

www.brichemsteel.com Fax: 001 (780) 469-6986 Tel: 001 (780) 469-6603

Product: Seamless Carbon Steel Pipe

Product Heat Number: BSM-0643

Product Size:

**NPS 24 SCH60** 

Production Date:

January 9, 2013

Production Method: Hot Expansion

Product Standards:

Product Heat Treatment: As-rolled

ASME B36.10-2004, ASTM/ASME A/SA106-2011 Grade B NDE, A/SA53-2012 Grade B Type S, NACE MR0175-2009, MR0103-2010

Product Markings: .BRI-STEEL MFG ASTM/ASME A/SA106 GR B A/SA53 GR B NPS 24 SCH60 HEAT BSM-0643 (PIPE # LENGTH MASS) 296.4lb/ft NDE SMLS NACE MR0175 2013/01 MADE IN CANADA.

Plain End	*	Pass	Pass	Pass	Pass	Pass	<20	<b>%</b>	296.40	DRL	5	SCH60	24	Heat	BSM-0643
Condition		ASTM E309	ASTM E213	WT	OD	Insp.	Gauss	μR/hr	lb/ft	Length	Pieces	Thickness	NPS	Test Type	Heat
End	HydroTest	ET	UT	UT		Visual	Res.Mag.	Geiger	Mass			Wall			
			e Testing	Destructiv	Non-E						S	Product Detail			

	1				-		
Chemical Analysis (wt%)							
Chemical Analysis (wt%)	Chemical Analysis (wt%)	Themical Analysis (wt%)	Chemical Analysis (wt%)	hemical Analysis (wt%)	Chemical Analysis (wt%)	hemical Analysis (wt%)	
Analysis (wt%)	Analysis (wt%)						
wt%)							
							CF

	BSM-0643 Heat	Heat		
	Heat	Test Type		
	Ferrite & Pearlite	Microstructure		
	73	HRBW	Hardness	
	Pass	Flattening Test		Mechar
Longitudinal; 38.1mm x WT	Transverse; 38.1mm x WT	50mm GL	Tension Test	Mechanical Properties
44,400	50,000	psi	Yield (Rt0.5)	
44,500	49,100	psi	Yield (Rp0.2)	
64,000	66,000	psi	Tensile (Rm)	
0.69	0.76	(Rt0.5/Rm)	T/Y	
64	63	%	Elongation (A)	

Additional Details:

results meet the corresponding requirements. Inc. in accordance with ASTM/ASME A/SA106-2011, A/SA53-2012 and the purchase order requirements, and that the ✓ We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing

Service, and NACE MR0103-2010 Section 2.1. This pipe product meets the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3 Sour

No weld repairs have been performed on this product.

√ This product has not come into contact with mercury during the Bri-Steel Manufacturing processes

 $\checkmark$  This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1.

\*Note that this product was hydrotested to 1000 psi for 5 seconds.

Mill Test Certificate approved by:

Kenton Dechant, P.Eng. 2013 Jan 18

Manager of Quality and R&D