

Mill Test Certificate

2125-64 Avenue, Edmonton, AB Canada T6P 1Z4 **Bri-Steel Manufacturing Inc.**

Fax: 001 (780) 469-6986 Tel: 001 (780) 469-6603 www.brichemsteel.com

Product: Seamless Carbon Steel Pipe

Product Heat Number:

BSM-0675

Production Method: Hot Expansion

Product Heat Treatment: As-rolled

Product Size:

NPS 24 STD

Production Date:

January 31, 2013

Product Standards: ASME B36.10-2004, API 5L-44th Ed. Grade B PSL1, ASTM/ASME A/SA106-2011 Grade B NDE, A/SA53-2012 Grade B Type S, NACE MR0175-2009, MR0103-2010

Product Markings: .BRI-STEEL MFG <API> 5L-0898 API 5L GR B PSL1 ASTM/ASME A/SA106 GR B A/SA53 GR B NPS 24 STD HEAT BSM-0675 (PIPE # LENGTH MASS) 94.621b/ft NDE 740 PSI SMLS NACE MR0175 2013/01 MADE IN CANADA.

	8790-MSB	000	Heat					
	Heat		lest Type	1				
	24 STD 23 DRL		NPS					
			Thickness		Wall		Product Details	
			Pieces				ils	
			Length					
	94.62		lb/ft		Mass			
	ŝ		μR/hr		Geiger			
	<20		Gauss		Res.Mag.			
	Pass		Insp.		Visual			
	Pass		8				Non-Des	
	Pass		¥,		TU		Destructive	
0.0000000000000000000000000000000000000	Pass		ASTM F213		UT.	c	esting	
	Pass		ASTM F309		E			
	Pass	1 .00000	09 740 nsi/5s	1	HydroTest			
	37.5° Bevel	Condition	Condition		End			

	E	-	Г				Г
	BSM-0675		неат	-		22 122 122 122 123 123 123 123 123 123 1	
Vacuum Degas; Fully Killed	Blast Furnace; EAF; Ladle Refining;		Steelmaking Method	?			
Product	Heat		Analysis				
0.21	0.20		0				
0.94	0.90		S				
0.008	0.013		Ъ				
0.006	0.004		S	36			Chemical Analysis (wt%
0.22	0.24		S:				Analysis
0.04	0.04		₽				Wt%)
0.07	0.08		5				
0.01	0.01		<u></u> ≤				
0.03	0.04		Z.				
0.004	1		<				
0.001	ı		=!				
0.001	ı		25				
0.0004	0.0003						
0.38		1/		5	2		
0.39	r	10001	(050)	C	2		

	BSM-06/5		Heat		
	Heat	11	Test Type		
	Ferrite & Pearlite		Microstructure		
	76		HRRW	Hardness	
	Pass	יימרניווון פיוריוו	Flattening Test		Mechar
Longitudinal; 38.1mm x WT	Transverse; 38.1mm x WT	COLLINICE	50mm G	Tension Test	Mechanical Properties
49,500	44,900	psi	2	Yield (Rt0.5)	
49,200	44,600	psi	5	Yield (Rp0.2)	
70,000	69,500	psi	5)	Tensile (Rm)	
0.71	0.65	(KtU.5/Km)	(750 7 /5 -1	Υ/Τ	
37	46	%	2	Elongation (A)	

Additional Details:

and that the results meet the corresponding requirements. Inc. in accordance with API 5L-44th Ed., ASTM/ASME A/SA106-2011, A/SA53-2012 and the purchase order requirements, ✓ We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing

Service, and NACE MR0103-2010 Section 2.1. ✓ This pipe product meets the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3 Sour

No weld repairs have been performed on this product.

√ This product has not come into contact with mercury during the Bri-Steel Manufacturing processes.

 \checkmark This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1.

Mill Test Certificate approved by:

2013 Feb 7

Kenton Dechant, P.Eng. Manager of Quality and R&D