

## Mill Test Certificate

**Bri-Steel Manufacturing Inc.** 

2125-64 Avenue, Edmonton, AB Canada T6P 1Z4 Fax: 001 (780) 469-6986 www.brichemsteel.com Tel: 001 (780) 469-6603

Product: Seamless Carbon Steel Pipe

Product Heat Number: BSM-0720

Product Size:

NPS 20 STD

Production Date:

February 18, 2013

Production Method: **Hot Expansion** 

Product Markings:

Product Standards:

Product Heat Treatment: As-rolled

ASME B36.10-2004, API 5L-44th Ed. Grade B PSL1, ASTM/ASME A/SA106-2011 Grade B NDE, A/SA53-2012 Grade B Type S, NACE MR0175-2009, MR0103-2010

BSM-0720 Heat 20	Heat Test Type NPS Thi		Floud
STD	Thickness Pi	Wall	Flounct Details
4	Pieces L		
DRL	Length	212	
78.60	lb/ft	Mass	
\$	μR/hr	Geiger	
<20	Gauss	Res.Mag.	
Pass	Insp.	Visual	
Pass	OD		Non-Dest
Pass	WT	TU	estructive in
Pass	ASTM E213	TU	esting
Pass	M E213 ASTM E309	ET	
Pass	910 psi/5s	HydroTest	
37.5° Bevel	Condition	End	

.BRI-STEEL MFG <API> 5L-0898 API 5L GR B PSL1 ASTM/ASME A/SA106 GR B A/SA53 GR B NPS 20 STD 0.375 inchWT HEAT BSM-0720 (PIPE # LENGTH MASS) 78.61b/ft NDE 910 PSI SML5 NACE MR0175 2013/02 MADE IN CANADA.

Vacuum Degas; Fully Killed Product 0.21 0.84 0.010 0.011 0.22 0.05 0.08 0.02 0.05 0.002 0.001 0.001	Heat	Steelmaking Method Blast Furnace: EAF: Ladle Refining:	Analysis	C 0.19	Mn 0.85		Chemical Analysis (wt%)  S Si Cr 0.012 0.22 0.09	Analysis Si 0.22	(wt%) Cr	Cu	Mo	. <u>z.</u>	<	· =	Nb	B 0.0004	(IIW)	1
ng; Heat 0.19 0.85 0.009 0.012 0.22 0.05 0.05 0.02	Heat	Steelmaking Method	Analysis	C	Mn	Р	S	Si	<del>ر</del>	C	Mo	Z.	<	=!	Nb	σ.		(E)
Vacuum Degas; Fully Killed   Product   0.21   0.84   0.010   0.011   0.22   0.05   0.08   0.02   0.05   0.002   0.001   0.001   0.0001	RSM-0720	Blast Furnace; EAF; Ladle Refining;	Heat	0.19	0.85	0.009	0.012	0.22	0.05	0.05	0.02	-		t	t	0.0004	3	ı
	001	Vacuum Degas; Fully Killed	Product	0.21	0.84	0.010	0.011	0.22	0.05	0.08	0.02	0.05	0.002	0.001	0.001	0.0001		0.37

				Mechan	Mechanical Properties					
			Hardness		Tension Test	Yield (Rt0.5)	Yield (Rp0.2)	Tensile (Rm)	Τ/γ	Elongation (A)
Heat	Test Type	Microstructure	HRBW	Flattening Test	50mm GL	psi	psi	psi	(Rt0.5/Rm)	%
BSM-0720 Heat	Heat	Ferrite & Pearlite	74	Pass	Transverse; 38.1mm x WT	41,600	40,100	70,000	0.59	43
			3		Longitudinal; 38.1mm x WT	44,900	44,500	70,500	0.64	40

Additional Details:

and that the results meet the corresponding requirements. Inc. in accordance with API 5L-44th Ed., ASTM/ASME A/SA106-2011, A/SA53-2012 and the purchase order requirements, ✓ We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing

Service, and NACE MR0103-2010 Section 2.1 √ This pipe product meets the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3 Sour

No weld repairs have been performed on this product.

√ This product has not come into contact with mercury during the Bri-Steel Manufacturing processes

√ This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1.

Mill Test Certificate approved by:

Manager of Quality and R&D Kenton Dechant, P.Eng.

2013 Feb 22