

## Mill Test Certificate

Bri-Steel Manufacturing Inc.

2125-64 Avenue, Edmonton, AB Canada T6P 1Z4 Fax: 001 (780) 469-6986 www.brichemsteel.com Tel: 001 (780) 469-6603

Product: Seamless Carbon Steel Pipe

Product Heat Number: BSM-0732

Product Size:

NPS 20 TRUE80

Production Date:

February 21, 2013

Production Method: Hot Expansion Product Heat Treatment: As-rolled

Product Standards: ASME B36.10-2004, ASTM/ASME A/SA106-2011 Grade B/C NDE, A/SA53-2012 Grade B Type S, NACE MR0175-2009, MR0103-2010

**Product Markings:** .BRI-STEEL MFG ASTM/ASME A/SA106 GR B/C A/SA53 GR B NPS 20 TRUE80 1.031 inchWT HEAT BSM-0732 (PIPE # LENGTH MASS) 208.9Ib/ft NDE SMLS NACE MR0175 2013/02 MADE IN CANADA.

|                                     | Т                  |    | T                       | ٦ |                           | Т                   | -         | Т                       |
|-------------------------------------|--------------------|----|-------------------------|---|---------------------------|---------------------|-----------|-------------------------|
| BSM-0732                            | Heat               | :  |                         |   | BSM-0732                  | Heat                |           |                         |
| Blast Furna                         | Steel              | ,  |                         |   | Heat                      | Test Type           |           |                         |
| Blast Furnace; EAF; Ladle Refining; | Steelmaking Method |    |                         |   | NPS 20 TRUE80 1.031 in.WT | Product Size        | 29        | Product Details         |
| Heat                                | Analysis           |    |                         |   | WT 2                      | Pieces              |           | tails                   |
| 0.20                                | 0                  |    |                         |   | _                         | +                   |           |                         |
| 0.94                                | Mn                 |    |                         |   | DRL                       | Length              |           |                         |
| 0.014                               | P                  |    |                         |   | 208.90                    | lb/ft               | Mass      |                         |
| 0.002                               | S                  |    | Chemical Analysis (wt%) |   | Ġ                         | μR/hr               | Geiger    |                         |
| 0.32                                | Si                 |    | Analysis                |   | <20                       | Gauss               | Res.Mag.  |                         |
| 0.05                                | Ç                  |    | wt%)                    |   | 0                         | SSI                 | /lag.     |                         |
| 0.04                                | Cu                 |    |                         |   | Pass                      | insp.               | Visual    |                         |
| 0.01                                | Μo                 |    |                         |   | Pass                      | OD                  |           | Nor                     |
| 0.04                                | Z.                 |    |                         |   | Pa                        | 8                   | _ ر       | Non-Destructive Testing |
| 0.003                               | <                  |    |                         |   | Pass                      | /T /                | TU        | ctive Te                |
| 0.003   0.002                       | =                  |    |                         |   | Pass                      | ASTM E213 ASTM E309 | TU        | sting                   |
| 0.001                               | Nb                 |    |                         |   | Pass                      | ASTM E30            | ET        |                         |
| 0.0002                              | В                  |    |                         |   | *                         | 99                  | HydroTest |                         |
| 1                                   | (WII)              | CE |                         |   |                           | _                   | Test      |                         |
| 1                                   | (CSA)              | CE |                         |   | Plain End                 | Condition           | End       |                         |

|                           | BSM-0732                | Heat            |                |                       |  |
|---------------------------|-------------------------|-----------------|----------------|-----------------------|--|
|                           | BSM-0732 Heat           | Test Type       |                |                       |  |
|                           | Ferrite & Pearlite      | Microstructure  |                |                       |  |
|                           | 74                      | HRBW            | Hardness       |                       |  |
|                           | Pass                    | Flattening Test |                | Mechar                |  |
| Longitudinal; 38.1mm x WT | Transverse; 38.1mm x WT | 50mm GL         | Tension Test   | Mechanical Properties |  |
| 45,000                    | 45,500                  | psi             | Yield (Rt0.5)  |                       |  |
| 44,900                    | 42,700                  | psi             | Yield (Rp0.2)  |                       |  |
| 69,000                    | 70,500                  | psi             | Tensile (Rm)   |                       |  |
| 0.65                      | 0.65                    | (Rt0.5/Rm)      | Υ/Τ            |                       |  |
| 57                        | 60                      | %               | Elongation (A) |                       |  |

Vacuum Degas; Fully Killed

Product 0.19 0.95 0.014 0.002 0.32

0.04

0.05

0.03

0.02

0.003 | 0.004 | 0.001 | 0.0002

0.36

0.37

## Additional Details:

- results meet the corresponding requirements. Inc. in accordance with ASTM/ASME A/SA106-2011, A/SA53-2012 and the purchase order requirements, and that the We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing
- Service, and NACE MR0103-2010 Section 2.1. This pipe product meets the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3 Sour
- No weld repairs have been performed on this product.
- This product has not come into contact with mercury during the Bri-Steel Manufacturing processes
- √ This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1.

\*Note that this product was hydrotested to 1000 psi for 5 seconds.

Mill Test Certificate approved by:

Kenton Dechant, P.Eng.

2013 Mary

Manager of Quality and R&D