

## Mill Test Certificate

Bri-Steel Manufacturing Inc.

2125-64 Avenue, Edmonton, AB Canada T6P 1Z4 Fax: 001 (780) 469-6986 www.brichemsteel.com Tel: 001 (780) 469-6603

Product: Seamless Carbon Steel Pipe

Product Heat Number:

NPS 24 SCH 60

Production Date:

Production Method: Hot Expansion

April 2, 2013

BSM-0802

**Product Heat Treatment:** As-rolled

Product Size:

Product Standards: ASME B36.10-2004, ASTM/ASME A/SA106-2011 Grade B NDE, A/SA53-2012 Grade B Type S, NACE MR0175-2009, MR0103-2010

**Product Markings:** .BRI-STEEL MFG ASTM/ASME A/SA106 GR B A/SA53 GR B NPS 24 SCH 60 0.969 inchWT HEAT BSM-0802 (PIPE # LENGTH MASS) 238.11b/ft NDE SMLS NACE MR0175 2013/04 MIADE IN CANADA.

BSM-0802	Heat		
)2 Heat	Test Type		
NPS 24 SCH 60 0.969 in.WT	e Product Size		Product Detail
7	Pieces		ls
DRL	Length		
238.10	lb/ft	Mass	
<5	μR/hr	Geiger	
<20	Gauss	Res.Mag.	
Pass	Insp.	Visual	
Pass	OD		Non-I
Pass	TW	TU	Destructive -
Pass	ASTM E213	TU	Testing
Pass	ASTM E309	ET	
*		HydroTest	
Plain End	Condition	End	

2000	BSM-0802			
Vacuum Degas; Fully Killed	Blast Furnace; EAF; Ladle Refining;	Steelmaking Method		
Product	Heat	Analysis		
0.20	0.19	С		
0.86	0.88	Mn		
0.012	0.010	P		
0.012 0.007	0.006	S		Chemica
7 0.24	0.24	Si		Chemical Analysis (wt%)
0.09	0.07	Cr		(wt%)
0.07	0.07	Cu		
0.01	0.02	Mo		
0.06	0.06	N:		
0.002	1	<		
0.001	1	Ti		
0.001	-	Nb		
0.0001	0.0003	В		
0.37	1	(IIW)	æ	
0.38		(CSA)	Œ	

5	RS.			
0000	M-0802	Heat		
11000	Heat t	Test Type		
C	Ferrite & Pearlite	Microstructure		
G	89	HRBW	Hardness	
1 833	Dass	Flattening Test		Mechar
Longitudinal; 38.1mm x WT	Transverse; 38.1mm x WT	50mm GL	Tension Test	Mechanical Properties
39,700	44,700	psi	Yield (Rt0.5)	
38,200	45,400	psi	Yield (Rp0.2)	
66,500	67,500	psi	Tensile (Rm)	
0.60	0.66	(Rt0.5/Rm)	Τ/γ	
55	52	%	Elongation (A)	
	Longitudinal; 38.1mm x WT 39,700 38,200 66,500 0.60	44,700 45,400 67,500 0.66   39,700 38,200 66,500 0.60	Test Type     Microstructure     HRBW     Flattening Test     50mm GL     psi     psi     psi     (Rt0.5/Rm)       Heat     Ferrite & Pearlite     68     Pass     Transverse; 38.1mm x WT     44,700     45,400     67,500     0.66       Longitudinal; 38.1mm x WT     39,700     38,200     66,500     0.60	Test Type     Microstructure     Hardness     Tension Test     Yield (Rt0.5)     Yield (Rp0.2)     Tensile (Rm)     Y/T     Elongation (Rt0.5/Rm)     %       Heat     Ferrite & Pearlite     68     Pass     Transverse; 38.1mm x WT     44,700     45,400     67,500     0.66     52       Longitudinal; 38.1mm x WT     39,700     38,200     66,500     0.60     55

	BSM-0802	Heat		
	E .	Standard	Test	
	1	Sample Details	Impact Test	
		Dē.	Temp	
	1	_		
	,	_	Impact	
	ı	J	Energy	
	1	AVG		
	,	%	% Shear	
	1	%		
The second secon	1	%		
	1	AVG		
	1	mm		
	1	mm	Lateral Expansion	
	1	mm		
	1	AVG		

## Additional Details:

results meet the corresponding requirements Inc. in accordance with ASTM/ASME A/SA106-2011, A/SA53-2012, and the purchase order requirements, and that the ✓ We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing

Service, and NACE MR0103-2010 Section 2.1. √ This pipe product meets the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3 Sour

- No weld repairs have been performed on this product.
- ✓ This product has not come into contact with mercury during the Bri-Steel Manufacturing processes
- √ This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1.

\*Note that this product was hydrotested to 1000 psi for 5 seconds.

Mill Test Certificate approved by:

2013 Apr 12

Manager of Quality and R&D Kenton Dechant, P.Eng.