

## Mill Test Certificate

Bri-Steel Manufacturing Inc.

2125-64 Avenue, Edmonton, AB Canada T6P 1Z4 Fax: 001 (780) 469-6986 Tel: 001 (780) 469-6603

www.brichemsteel.com

Seamless Carbon Steel Pipe Product Heat Number: BSM-0828 Product Size: NPS 24 XS

Product:

Production Date: April 10, 2013

Production Method: **Hot Expansion** Product Heat Treatment: As-rolled

Product Standards: ASME B36.10-2004, API 5L-44th Ed. Grade B PSL1, ASTM/ASME A/SA106-2011 Grade B NDE, A/SA53-2012 Grade B Type S, NACE MR0175-2009, MR0103-2010

Product Markings: .BRI-STEEL MFG <API> 5L-0898 API 5L GR B PSL1 ASTM/ASME A/SA106 GR B A/SA53 GR B NPS 24 XS 0.5 inchWT HEAT BSM-0828 (PIPE # LENGTH MASS) 125.5Ib/ft NDE 970 PSI SMLS NACE MR0175 2013/04 MADE IN CANADA

|  |                     | Т                 | _         |                |
|--|---------------------|-------------------|-----------|----------------|
|  | BSM-0828            | Heat              |           |                |
|  | Heat                | Test Type         |           |                |
|  | NPS 24 XS 0.5 in.WT | Product Size      |           | Product Detail |
|  | 2                   | Pieces            |           | S              |
|  | DRL                 | Length            |           |                |
|  | 125.50              | lb/ft             | Mass      |                |
|  | S                   | μR/hr             | Geiger    | 10             |
|  | <20                 | Gauss             | Res.Mag.  |                |
|  | Pass                | Insp.             | Visual    |                |
|  | Pass                | OD                |           | Non-D          |
|  | Pass                | TW                | TΠ        | Destructive 1  |
| Company of the Compan | Pass                | ASTM E213         | TU        | esting         |
| CONTRACTOR  | Pass                | ASTM E309         | T3        |                |
|  | Pass                | 4 E309 970 psi/5s | HydroTest |                |
|  | 37.5° Bevel         | Condition         | End       |                |
|  |                     |                   |           |                |

|            |                            |                                     |                    |    | _                       |
|------------|----------------------------|-------------------------------------|--------------------|----|-------------------------|
|            |                            | RSM-0878                            | Heat               |    |                         |
|            | Vacuum Degas; Fully Killed | Blast Furnace; EAF; Ladle Refining; | Steelmaking Method |    |                         |
|            | Product                    | Heat                                | Analysis           |    |                         |
|            | 0.20                       | 0.18                                | C                  |    |                         |
|            | 0.86                       | 0.87                                | Mn                 |    |                         |
|            | 0.016                      | 0.011                               | P                  |    |                         |
|            | 0.016 0.005                | 0.008                               | S                  |    | Chemical Analysis (wt%) |
|            | 0.24                       | 0.24                                | Si                 |    | Analysis                |
|            | 0.04                       | 0.05                                | Ç                  |    | (wt%)                   |
|            | 0.09                       | 0.06                                | Cu                 |    |                         |
|            | 0.01                       | 0.02                                | Mo                 |    |                         |
| The second | 0.03                       | 0.04                                | Z.                 |    |                         |
|            | 0.002                      | Е                                   | <                  |    |                         |
|            | 0.001                      | ,                                   | ∄                  |    |                         |
|            | 0.001                      | E                                   | Nb                 |    |                         |
|            | 0.0001                     | 0.0003                              | В                  |    |                         |
|            | 0.36                       | 10                                  | (IIW)              | Œ  |                         |
|            | 0.37                       | 1                                   | (CSA)              | CE |                         |

|          |           |                    |          | Iviecnar        | Mechanical Properties     |               |              |            |                |
|----------|-----------|--------------------|----------|-----------------|---------------------------|---------------|--------------|------------|----------------|
|          |           |                    | Hardness |                 | Tension Test              | Yield (Rt0.5) | Tensile (Rm) | T/A        | Elongation (A) |
| Heat     | Test Type | Microstructure     | HRBW     | Flattening Test | 50mm GL                   | psi           | psi          | (Rt0.5/Rm) | %              |
| BSM-0828 | 328 Heat  | Ferrite & Pearlite | 72       | Pass            | Longitudinal; 38.1mm x WT | 40,700        | 67,000       | 0.61       | 48             |
|          |           |                    |          |                 |                           |               |              |            |                |

|          | T              | _               |  |
|----------|----------------|-----------------|--|
| BSM-0828 | Heat           |                 |  |
| 1        | Standard       | Test            |  |
| Ť        | Sample Details | Impact Test     |  |
| I        | °C             | Temp            |  |
| ı        | _              |                 |  |
| ı        | j              | Impact          |  |
| 16       | _              | Energy          |  |
|          | AVG            |                 |  |
| 1        | %              |                 |  |
|          | %              | 4S %            |  |
| t        | %              | Shear           |  |
| ı        | AVG            |                 |  |
| t        | mm             |                 |  |
| ı        | mm             | Lateral E       |  |
|          | mm             | <b>kpansion</b> |  |
| 1        | AVG            |                 |  |

## Additional Details:

- and that the results meet the corresponding requirements. Inc. in accordance with API 5L-44th Ed., ASTM/ASME A/SA106-2011, A/SA53-2012, and the purchase order requirements, ✓ We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing
- Service, and NACE MR0103-2010 Section 2.1. √ This pipe product meets the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3 Sour
- ✓ No weld repairs have been performed on this product.
- ✓ This product has not come into contact with mercury during the Bri-Steel Manufacturing processes
- $\checkmark$  This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1.

Mill Test Certificate approved by:

Manager of Quality and R&D Kenton Dechant, P.Eng.