

Mill Test Certificate

Bri-Steel Manufacturing Inc.

2125-64 Avenue, Edmonton, AB Canada T6P 1Z4 Tel: 001 (780) 469-6603 Fax: 001 (780) 469-6986

www.brichemsteel.com

Product: Seamless Carbon Steel Pipe

Production Method:

Hot Expansion

Product Heat Number: BSM-0845

Product Size:

Size: NPS 20 STD

8

Production Date: April 18, 2013

As-rolled

Product Heat Treatment:

Product Standards: ASME B36.10-2004, API 5L-44th Ed. Grade B PSL1, ASTM/ASME A/SA106-2011 Grade B/C NDE, A/SA53-2012 Grade B Type S, NACE MR0175-2009, MR0103-2010

Product Markings: .BRI-STEEL MFG <API> 5L-0898 API 5L GR B PSL1 ASTM/ASME A/SA106 GR B/C A/SA53 GR B NPS 20 STD 0.375 inchWT HEAT BSM-0845 (PIPE # LENGTH MASS) 78.6ib/ft NDE 910 PSI SMLS NACE MR0175 2013/04 MADE IN CANADA.

<u></u>			
3SM-0845	Heat		
Heat	Test Type		
NPS 20 STD 0.375 in.WT	Product Size		Product Detail
9	Pieces		S
DRL	Length		
78.60	lb/ft	Mass	
Ġ.	μR/hr	Geiger	
<20	Gauss	Res.Mag.	
Pass	Insp.	Visual	
Pass	OD		Non-E
Pass	WT	TU	Destructive '
Pass	ASTM E213	UT	Testing
Pass	ASTM E309	ET	
Pass	910 psi/5s	HydroTest	
37.5° Bevel	Condition	End	
	NPS 20 STD 0.375 in.WT 9 DRL 78.60 <5 <20 Pass Pass Pass Pass Pass Pass Pass	Test Type Product Size Pieces Length lb/ft μR/hr Gauss Insp. OD WT ASTM E213 ASTM E309 910 psi/5s Heat NPS 20 STD 0.375 in.WT 9 DRL 78.60 <5 <20 Pass Pass Pass Pass Pass Pass	Test TypeProduct SizePiecesLengthIb/ftμR/hrGaussVisualUTUTUTETHydroTestHeatNPS 20 STD 0.375 in.WT9DRL78.60<5

Heat	Steelmaking Method	Analysis	0 00 0	Mn		Chemical Analysis (wt%) S Si Cr	Analysis Si	(wt%) Cr	Cu	Mo	N:	<	- п	Nb	B 0003	CE (IIW)	
Heat	akin	Analysis	С	Mn	P	S	Si	Cr	Cu	Mo	N:	٧	Ti	Nb	В	(WII)	
BCM-0845	Blast Furnace; EAF; Ladle Refining;	Heat	0.20	0.89	0.008	0.009	0.25	0.03	0.08	0.02	0.04				0.0003	1	
0014100	Vacuum Degas; Fully Killed	Product	0.21	0.89	0.011	0.009	0.24	0.03	0.07	0.03	0.04	0.003	0.001	0.001	0.0001	0.38	_

Heat Test Type Microstructure Hardness Flattening Test Flatten
st Type Microstructure Hardness Flattening Test Forrite & Pearlite 79 Pass Longitudinal; 38.1mm x WT 48,300 74,000 0.65 4
Hardness Hardness Tension Test Flores
Tension Test Yield (Rt0.5) Tensile (Rm) Y/T Elongary
Tension Test Yield (Rt0.5) Tensile (Rm) Y/T Elonga:
Test Yield (Rt0.5) Tensile (Rm) Y/T Elongar n GL psi psi (Rt0.5/Rm) 9 18.1mm x WT 48,300 74,000 0.65 4
d (Rt0.5) Tensile (Rm) Y/T Elonga psi psi (Rt0.5/Rm) 9 8,300 74,000 0.65 4
ile (Rm) Y/T Elonga psi (Rt0.5/Rm) 9 ,,000 0.65 4
n) Elonga
Elongation (A) % 43

n mn	mm	AVG	%	%	%	AVG	J	_	_	Οē	Sample Details	Standard	Heat
		ļ	% Shear	% S			Energy	Impact		Temp	Impact Test	Test	

Additional Details:

- and that the results meet the corresponding requirements. Inc. in accordance with API 5L-44th Ed., ASTM/ASME A/SA106-2011, A/SA53-2012, and the purchase order requirements, ✓ We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing
- Service, and NACE MR0103-2010 Section 2.1. ✓ This pipe product meets the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3 Sour
- No weld repairs have been performed on this product.
- √ This product has not come into contact with mercury during the Bri-Steel Manufacturing processes.
- \checkmark This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1.

Mill Test Certificate approved by:

2013 pr 24 Kenton Dechant, P.Eng. Manager of Quality and R&D