

Mill Test Certificate

Bri-Steel Manufacturing Inc.

2125-64 Avenue, Edmonton, AB Canada T6P 1Z4 Fax: 001 (780) 469-6986 Tel: 001 (780) 469-6603

www.brichemsteel.com

Product: Seamless Carbon Steel Pipe

Product Heat Number: BSM-0857

Hot Expansion

Product Size: NPS 24 STD

Production Date:

Production Method:

Product Heat Treatment:

April 25, 2013

As-rolled

Product Standards: ASME B36.10-2004, API 5L-44th Ed. Grade B PSL1, ASTM/ASME A/SA106-2011 Grade B/C NDE, A/SA53-2012 Grade B Type S, NACE MR0175-2009, MR0103-2010

Product Markings: BRI-STEEL MFG <API> 51-0898 API 5L GR B PSL1 ASTM/ASME A/SA106 GR B/C A/SA53 GR B NPS 24 STD 0.375 inchWT HEAT BSM-0857 (PIPE # LENGTH MASS) 94.62lb/ft NDE 740 PSI SMLS NACE MR0175 2013/04 MADE IN CANADA.

				Т
	BSM-0857	Heat		
	Heat	Test Type		
	NPS 24 STD 0.375 in.WT	Product Size		Product Detail
	13	Pieces		S
	DRL	Length		
	94.62	lb/ft	Mass	
	Ĝ	μR/hr	Geiger	
	<20	Gauss	Res.Mag.	
	Pass	Insp.	Visual	
St. Transfer and the state of t	Pass	OD		Non-E
The second secon	Pass	WT	TU	Destructive 1
	Pass	ASTM E213 /	TU	esting
	Pass	ASTM E309	ET	
	Pass	740 psi/5s	HydroTest	
	32.5° Bevel	Condition	End	

Vacuum Degas; Fully Killed Product 0.21 0.88 0.012 0.008 0.24 0.03 0.07 0.03 0.04	RSMI-0857 Blast Furnace; EAF; Ladle Refining; Heat 0.18 0.88 0.009 0.004 0.25 0.04 0.09 0.02 0.05	Heat Steelmaking Method Analysis C Mn P S Si Cr Cu Mo Ni		Chemical Analysis (wt%)
0 210		Р		Ch
0.008	0.004	S		nemical +
0.24	0.25	Si		Analysis (
0.03	0.04	Cr		wt%)
0.07	0.09	Cu		
0.03	0.02	Mo		
0.04	0.05	Z.		
0.002	,	<		
0.001	1	ij		
0.001	1	Nb		
0.0001	0.0003	8		
0.38	ı	(IV)	Œ	
0.38	ï	(CSA)	Œ	

Test TypeMicrostructureHardnessTension TestYield (Rt0.5)Tensile (Rm)Y/TElongation (A)HeatFerrite & Pearlite78PassLongitudinal; 38.1mm x WT45,00072,5000.6240
Hardness Tension Test Yield (Rt0.5) Tensile (Rm) HRBW Flattening Test 50mm GL psi psi (Rt0.5) 78 Pass Longitudinal; 38.1mm x WT 45,000 72,500 (10.5)
Tension Test Yield (Rt0.5) Tensile (Rm)
Tension Test Yield (Rt0.5) Tensile (Rm) 50mm GL psi psi (Rt0.5) Longitudinal; 38.1mm x WT 45,000 72,500 (10.5)
Yield (Rt0.5) Tensile (Rm) psi psi 45,000 72,500
(Rt0.5) Tensile (Rm) (Rt0 psi (Rt0 ,000 72,500 (
Rm) (RtC
Y/T Elongation (A) (Rt0.5/Rm) % 0.62 40
Elongation (A) %

BSM-0857	Heat		
	Standard	Test	
3	Sample Details	Impact Test	
ı	Oē	Temp	
,	_		
	L	Impact	
	J	Energy	
	AVG		
	%		
r	%	% SI	
E	%	Shear	
ı	AVG		
£	mm		
1	mm	Lateral Ex	
	mm	xpansion	
ć.	AVG		

Additional Details:

- and that the results meet the corresponding requirements Inc. in accordance with API 5L-44th Ed., ASTM/ASME A/SA106-2011, A/SA53-2012, and the purchase order requirements, ✓ We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing
- Service, and NACE MR0103-2010 Section 2.1. √ This pipe product meets the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3 Sour
- No weld repairs have been performed on this product.
- This product has not come into contact with mercury during the Bri-Steel Manufacturing processes
- \checkmark This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1.

Mill Test Certificate approved by:

Kenton Dechant, P.Eng.

Manager of Quality and R&D