

Bri-Steel Manufacturing Inc.

2125-64 Avenue, Edmonton, AB Canada T6P 1Z4 Fax: 001 (780) 469-6986 Tel: 001 (780) 469-6603

Production Date:

May 3, 2013

www.brichemsteel.com

Mill Test Certificate

Product: Seamless Carbon Steel Pipe Product Heat Number: BSM-0882 Product Size: **NPS 24 XS**

Production Method:

Hot Expansion Product Heat Treatment:

As-rolled

Product Standards: ASME B36.10-2004, API 5L-44th Ed. Grade B PSL1, ASTM/ASME A/SA106-2011 Grade B NDE, A/SA53-2012 Grade B Type S, NACE MR0175-2009, MR0103-2010

Product Markings: BRI-STEEL MFG <API> 5L-0898 API 5L GR B PSL1 ASTM/ASME A/SA106 GR B A/SA53 GR B NPS 24 XS 0.5 inchWT HEAT BSM-0882 (PIPE # LENGTH MASS) 125.5Ib/ft NDE 970 PSI SMLS NACE MR0175 2013/05 MADE IN CANADA.

Pass Pass		Pass
OD WT	TW	OD WT ASTM E213 ASTM E309
UT	UT UT	UT UT ET
Non-Destruct	Non-Destructive Testing	Non-Destructive Testing

		,		
2000-14100	BSM_0883	Heat		
Vacuum Degas; Fully Killed	Blast Furnace; EAF; Ladle Refining;	Steelmaking Method		
Product	Heat	Analysis		
0.20	0.18	С		
0.86	0.87	Mn		
0.017	0.013	P		
0.005	0.004	S		Chemical
0.24	0.24	Si		Chemical Analysis (wt%)
0.04	0.04	C,	2303	(wt%)
0.09	0.04	Cn		
0.01	0.01	Mo		
0.03	0.04	Z.		
0.002	,	<		
0.001	-	П		
0.001	1	Nb		
0.0001	0.0004	В		
0.36		(WII)	Œ	
0.37		(CSA)	CE	

Heat Test Type Microstructure Hardness Ferrite & Pearlite 74 Pass Longitudinal; 38.1mm x WT 45,200 68,000 0.66 49	_			
Mechanical Properties Mechanical Properties Tension Test Microstructure Hardness Ferrite & Pearlite Pass Mechanical Properties Tension Test Form GL psi psi (R 45,200 68,000	BSM-0882	Heat		
Hardness Hardness Tension Test Yield (Rt0.5) Tensile (Rm) HRBW Flattening Test 50mm GL psi psi (R 74 Pass Longitudinal; 38.1mm x WT 45,200 68,000	Heat	Test Type		
Mechanical Properties Tension Test Flattening Test Pass Longitudinal; 38.1mm x WT Yield (Rt0.5) Yield (Rt0.5) Yield (Rt0.5) Flatte, (Rm) A 5,200 Flattening Test A 5,200 68,000	Ferrite & Pearlite	Microstructure		
rical Properties Tension Test 50mm GL Longitudinal; 38.1mm x WT Yield (Rt0.5) Yield (Rt0.5) Yeld (Rt0.5) Yeld (Rt0.5) 45,200 68,000	74	HRBW	Hardness	
Test Yield (Rt0.5) Tensile (Rm) I GL psi psi 8.1mm x WT 45,200 68,000	Pass	Flattening Test		Mechar
.5) Tensile (Rm) psi (R 68,000	Longitudinal; 38.1mm x WT	50mm GL	Tension Test	ical Properties
(Rm) (R (Rm) (R	45,200	psi	Yield (Rt0.5)	
Y/T Elongation (A) (Rt0.5/Rm) % 0.66 49	68,000	psi	Tensile (Rm)	
Elongation (A) %	0.66	(Rt0.5/Rm)	Τ/Υ	
	49	%	Elongation (A)	

-	Test	Impact Test	Temp		Impact	Energy			% S	Shear			Lateral I	sdxi	xpansior
Heat	Standard	Sample Details	°C	J	_	J	AVG	%	%	%	AVG	mm	mm		mm
BSM-0882		-	1	1	,	,	3	1	-	1	ı	1	1	-	1

Additional Details:

- and that the results meet the corresponding requirements. Inc. in accordance with API 5L-44th Ed., ASTM/ASME A/SA106-2011, A/SA53-2012, and the purchase order requirements, ✓ We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing
- Service, and NACE MR0103-2010 Section 2.1. √ This pipe product meets the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3 Sour
- No weld repairs have been performed on this product.
- This product has not come into contact with mercury during the Bri-Steel Manufacturing processes
- ✓ This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1.

Mill Test Certificate approved by:

Manager of Quality and R&D Kenton Dechant, P.Eng.

2013/May 9