

## Mill Test Certificate

2125-64 Avenue, Edmonton, AB Canada T6P 1Z4 Bri-Steel Manufacturing Inc.

Tel: 001 (780) 469-6603

Fax: 001 (780) 469-6986

www.bri-steel.com

Seamless Carbon Steel Pipe Product Heat Number: BSM-0903 Product Size: 20 X 0.700

Production Method:

Hot Expansion

Product:

Product Heat Treatment: As-rolled Certificate No.: MTR- 001233

Production Date:

Jul 10, 2014

Product Standards: ASME B36.10-2004, ASTM/ASME A/SA106-2013 Grade B/C NDE, A/SA53-2012 Grade B Type S, NACE MR0175-2009 MR0103-2010

Product Markings BRI-STEEL NPS 20 X 0.700 INCHWT SMLS 2014/07 NDE

HEAT BSM-0903 (PIPE # LENGTH MASS) 144.29lb/ft ASTM/ASME A/SA106 GR B/C A/SA53 GR B NACE MR0175/MR0103 MADE IN CANADA

|          |           | Product: Details     |        |        |        |        |           |        | N    | Non-Destructive Testin | tive Testing   |      |           |           |
|----------|-----------|----------------------|--------|--------|--------|--------|-----------|--------|------|------------------------|----------------|------|-----------|-----------|
| Heat     | Test Type | Product Size         | Pieces | Length | Mass   | Geiger | Res. Mag. | Visual | OD   | IN                     | UT             | 티    | HydroTest | End       |
|          |           |                      |        |        | lb/ft  | μR/hr  | Gauss     | Insp.  |      | TW                     | ASTM E213 ASTM | ASTM |           | Condition |
| BSM-0903 | Heat      | NPS 20 X 0.700in. WT | 20     | DRL    | 144.29 |        |           | Pass   | Pass | 1                      | Pass           | Pass | *         | Plain End |

|                      | BSM-0903                                   | Heat               | 00001                   |
|----------------------|--|--------------------|-------------------------|
|                      | ω  | )t                 |                         |
| Legas, Fully Stilled | Blast Furnace; EAF; Ladle Refining; Vacuum | Steelmaking Method |                         |
| Product              | Heat                                       | Test Type          |                         |
| 0.21                 | 0.20                                       | С                  |                         |
| 0.95                 | 0.96                                       | Mn                 |                         |
| 0.018                | 0.002                                      | P                  |                         |
| 0.009                | 0.007                                      | S                  | Chemical                |
| 0.31                 | 0.35                                       | Si                 | Chemical Analysis (wt%) |
| 0.05                 | 0.06                                       | Cr                 | wt%)                    |
| 0.07                 | 0.09                                       | Си                 |                         |
| 0.01                 | 0.09                                       | Mo                 |                         |
| 0.03                 | 0.03                                       | N:                 |                         |
| 0.003                | 0.006                                      | ٧                  |                         |
| 0.002                | 0.002                                      | П                  |                         |
| 0.002                | 0.003                                      | Nb                 |                         |
| 0.0002               | 0.0002                                     | В                  |                         |
| 0.39                 |  | CE(IIW)            |                         |
| 0.39                 | ,  | CE(CSA)            |                         |

|  |                            | _          |                 | _                     |
|--|----------------------------|------------|-----------------|-----------------------|
|  | BSM-0903                   |            | Heat            |                       |
|  | Heat                       |            | Test Type       |                       |
|  | Ferrite & Pearlite         |            | Microstructure  |                       |
|  | 80 HRBW                    |            | Hardness        |                       |
|  | Pass                       |            | Flattening Test |                       |
|  | Longitudinal; 38.1 mm x WT | 50mm GL    | Tension Test    | Mechanical Properties |
| The second secon | 44,200                     | psi        | Yield (Rt0.5)   |                       |
|  | 72,500                     | psi        | Tensile (Rm)    |                       |
|  | 0.61                       | (Rt0.5/Rm) | 1/4             |                       |
|  | 49                         | %          | Elongation (A)  |                       |

|     |             | 1         | 111 | ť   | 4     | C    | I. |     | 1        | ı      |   | L    |                |          | BSM-0903 |
|-----|-------------|-----------|-----|-----|-------|------|----|-----|----------|--------|---|------|----------------|----------|----------|
| AVG | mm          | mm        | mm  | AVG | %     | %    | %  | AVG | _        | J      | _ | ငိ   | Sample Details | Standard |          |
|     | l Expansion | Lateral E |     |     | Shear | % SI |    |     | t Energy | Impaci |   | Temp | Impact Test    | Test     | Heat     |

## Additional Details:

- ✓ We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing Inc. in results meet the corresponding requirements. accordance with ASTM/ASME A/SA106-2013 Grade B/C A/SA53-2012, and the purchase order requirements, and that the
- √ This pipe product meets the sour service requirements of NACE MR0175/ISO 15156-2;2009 Annex A2 for Region 3 Sour Service-2009 NACE MR0103-2010 Section 2.1
- ✓ No weld repairs have been performed on this product.
- $\checkmark$  This product has not come into contact with mercury during the Bri-Steel Manufacturing processes
- $\checkmark$  This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1.
- \* Note that this product was hydrotested to 1000 psi for 5 seconds

Mill Test Certificate approved by:

Inly. 14.2014

Tonya Lam, C.E.T.

Assistant QA Manager