

## Mill Test Certificate

2125-64 Avenue, Edmonton, AB Canada T6P 1Z4 Bri-Steel Manufacturing Inc.

Tel: 001 (780) 469-6603

Fax: 001 (780) 469-6986 www.brichemsteel.com

Production Date:

NPS 24 TRUE80

May 30, 2013

Product Heat Number: BSM-0953 Product Size:

Production Method: Hot Expansion Product Heat Treatment: As-rolled

Product:

Seamless Carbon Steel Pipe

Product Standards: ASME B36.10-2004, ASTM/ASME A/SA106-2011 Grade B/C NDE, A/SA53-2012 Grade B Type S, NACE MR0175-2009, MR0103-2010

**Product Markings:** BRI-STEEL MFG ASTM/ASME A/SA106 GR B/C A/SA53 GR B NPS 24 TRUE80 1.219 inchWT HEAT BSM-0953 (PIPE # LENGTH MASS) 296.4lb/ft NDE SMLS NACE MR0175 2013/05 MADE IN CANADA

Plain End	*	Pass	Pass	Pass	Pass	Pass	<20	Ġ	296.40	DRL	2	NPS 24 TRUE80 1.219 in.WT	Heat	BSM-0953
Condition		ASTM E309	ASTM E213 ASTM E309	TW	OD**	insp.	Gauss	μR/hr	lb/ft	Length	Pieces	Product Size	Test Type	Heat
End	HydroTest	ET	TU	TU		Visual	Res.Mag.	Geiger	Mass					
			esting	estructive T	Non-C						S	Product Detail		

Г	BS	Τ		
	BSM-0953	Heat		
Vacuum Degas; Fully Killed	Blast Furnace; EAF; Ladle Refining;	Steelmaking Method		
Product	Heat	Analysis		
0.20	0.22	0		
0.89	0.90	Mn		
0.016	0.013	P		
0.003		S		Chemical
0.30	0.32	Si		Chemical Analysis (wt%)
0.05	0.05	ς,		(wt%)
0.06	0.06	5		
0.01	0.00	Mo		
0.03	0.03	<u>Z</u> .		
0.005	0.004	<		2
0.002	0.003	Ti		
0.001	0.001	Nb		
0.0001	0.0001	В		
0.37	,	(IIW)	CE	
0.38	1	(CSA)	CE	

			-	_			_
DO A COTO	Heat			BSM-0953	Heat		
	Standard	Test		Heat	Test Type		
	Sample Details	Impact Test		Ferrite & Pearlite	Microstructure		
				79	HRBW	Hardness	
	)c	Temp		Pass	Flattening Test		7
	J				Test		/lechar
	_	Impact Energy		Longitudinal;		Tensi	Mechanical Properties
	J AVG	rgy		Longitudinal; 19.1mm x WT	50mm GL	Tension Test	S
	%			42,200	psi	Yield (Rt0.5)	
	%	% Shear	o/ Chan	200	Si.	Rt0.5)	
	%	ear		70,500	psi	Tensile (Rm)	
	AVG			00		(Rm)	
	mm	Lateral Expansion		0.60	(Rt0.5/Rm)	Т/4	
	mm			0	/Rm)	7	
	mm	pansion		48	%	Elongation (A)	
	AVG	1		3		ion (A)	

Additional Details:

BSM-0953

results meet the corresponding requirements. Inc. in accordance with ASTM/ASME A/SA106-2011, A/SA53-2012, and the purchase order requirements, and that the We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing

Service, and NACE MR0103-2010 Section 2.1. This pipe product meets the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3 Sour

No weld repairs have been performed on this product.

This product has not come into contact with mercury during the Bri-Steel Manufacturing processes

 $\checkmark$  This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1.

\*Note that this product was hydrotested to 1000 psi for 5 seconds.

\*\*OD Tolerances as per API

Mill Test Certificate approved by:

VOYON

Paul Sowden, T.T.

Assistant QA Manager