

Mill Test Certificate

2125-64 Avenue, Edmonton, AB Canada T6P 1Z4 Bri-Steel Manufacturing Inc.

Fax: 001 (780) 469-6986 Tel: 001 (780) 469-6603 www.brichemsteel.com

NPS 24 TRUE80

Production Date:

Product Size:

June 3, 2013

Production Method: Hot Expansion Product Heat Treatment: As-rolled

Product:

Seamless Carbon Steel Pipe

Product Heat Number:

BSM-0959

Product Standards: ASME B36.10-2004, ASTM/ASME A/SA106-2011 Grade B/C NDE, A/SA53-2012 Grade B Type S, NACE MR0175-2009, MR0103-2010

Product Markings: BRI-STEEL MFG ASTM/ASME A/SA106 GR B/C A/SA53 GR B NPS 24 TRUE80 1.219 inchWT HEAT BSM-0959 (PIPE # LENGTH MASS) 296.4lb/ft NDE SMLS NACE MR0175 2013/06 MADE IN CANADA.

	BSM-0959	חבמנ			
	Heat	rest Type	Task Time		
	NPS 24 TRUESO 1 219 in W/T	Product Size			Product Detail:
c	IJ	Pieces	!		ls
DVL	ם כו	Length			
230.40	200 40	lb/ft	IVIdos	Mace	
Ó	,	μR/hr	GEISEI	Coimor	
07>	200	Gauss	Kes.Iviag.	000000	
Pass		Insp.	visual	100	
Pass	,	OD**			Non-D
Pass	,	ΥT	_		Destructive Testini
Pass		ASTM E213	U	. 10	esting
Pass		M E213 ASTM E309	П		
*			HydroTest		
Plain End	000000000000000000000000000000000000000	Condition	End		

	Г		-	_	_	_	_
		BSM-0959		пеац			
	Vacuum Degas; Fully Killed	Blast Furnace; EAF; Ladle Refining;	7	Steelmaking Method			
	Product			Analysis			
	0.22	0.20		0	į		
	0.90	0.89		S			
	0.010 0.006	0.013		Ъ			
	0.006	0.002		S			Chemical Analysis (wt%)
	0.29	0.29		S			Analysis
	0.04	0.07	!	<u>ر</u>			(wt%)
	0.09	0.04	2	5			
	0.01	0.03	1	3			
	0.04	0.02		Z			
	0.004	0.001	*	<			
1	0.001	0.002	-	=!			
2000	0.001	0.001	JAN.	25			
20000	0.0001	0.0002	0	D			
0.00	0 39	1	(1144)	(111/4)	CF	2	
0.70	0.40	1	(COA)	(CCA)	CF	3	

				Mechar	Mechanical Properties				
			Hardness		Tension Test	Yield (Rt0.5)	Tensile (Rm)	Τ/γ	Elongation (A)
Heat	Test Type	Microstructure	HRBW	Flattening Test	50mm GL	<u>ps.</u>	ns.	(R+0 5/Rm)	0/
BSM_NOSO	10	Fourity o Desality				700	700	(mo.s/mil)	/0
GCGN-IAICO	пеат	rerrite & Pearlite	79	Pass	Longitudinal; 19.1mm x WT	49,600	71,500	0.69	48

		BSM-0959			Heat	
			2000	Crandara	Standard	lest
				ממוווסוב הבנמווס	Cample Details	Impact Test
		1		==	200	Temp
		-		J		
				J		Impact
				٦		Energy
		·		AVG		
				%		
		,		%		% S
		,		%		% Shear
		,		AVG		
				mm		
Section Company of the Section Co.	,	,		m m		Lateral E
	ı	ı		m m	1	xpansion
	ı			AVG		

Additional Details:

- Inc. in accordance with ASTM/ASME A/SA106-2011, A/SA53-2012, and the purchase order requirements, and that the results meet the corresponding requirements. $\checkmark~$ We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing
- Service, and NACE MR0103-2010 Section 2.1. This pipe product meets the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3 Sour
- No weld repairs have been performed on this product.
- This product has not come into contact with mercury during the Bri-Steel Manufacturing processes.
- \checkmark This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1.
- *Note that this product was hydrotested to 1000 psi for 5 seconds.
- **OD Tolerances as per API

Mill Test Certificate approved by:

South 10 100 JON 01

Paul Sowden, T.T.

Assistant QA Manager