

Mill Test Certificate

2125-64 Avenue, Edmonton, AB Canada T6P 1Z4 Bri-Steel Manufacturing Inc.

Tel: 001 (780) 469-6603

Fax: 001 (780) 469-6986 www.brichemsteel.com

NPS 18 SCH 120 Production Date: July 4, 2013

Production Method: Hot Expansion Product Heat Treatment: As-rolled Product:

Seamless Carbon Steel Pipe

Product Heat Number:

BSM-1049

Product Size:

Product Standards: ASME B36.10-2004, ASTM/ASME A/SA106-2011 Grade B NDE, A/SA53-2012 Grade B Type S, NACE MR0175-2009, MR0103-2010

Product Markings: BRI-STEEL MFG ASTM/ASME A/SA106 GR B A/SA53 GR B NPS 18 SCH 120 1.375 inchWT HEAT BSM-1049 (PIPE # LENGTH MASS) 244.1lb/ft NDE SMLS NACE MR0175 2013/07 MADE IN CANADA.

BSM-1049	Heat		
Heat	Test Type		
NPS 18 SCH 120 1.375 in.WT	Product Size		Product Detail
5	Pieces		5
DRL	Length		
244.10	lb/ft	Mass	
S	μR/hr	Geiger	
<20	Gauss	Res.Mag.	
Pass	insp.	Visual	
Pass	OD**		Non-l
Pass	WT	UT	Non-Destructive Testing
Pass	ASTM E213	TU	Testing .
Pass	ASTM E213 ASTM E309	ET	
*		HydroTest	
Plain End	Condition	End	

0.38	0.3/	2000.0	TOO.0	0.003	0.004	0.03	10.01	0.04	0.00	0.31	0.000	CTO.O	0.50	0.20	FIOURCE	vacuum pegas, runy nineu	
0.00	2	2000	000	2000		2	2	2	0 00	0		_		000	0.01	Vacuum Dogaca Fally Killad	DO TO
1	ı	0.0004	0.001	0.002	0.003	0.04	0.01	0.07	0.04	0.30	0.003	0.015	0.89	0.19	Heat	Blast Furnace; EAF; Ladle Refining;	RSM-1049
(CSA)	(IIW)	В	Nb	Ti	<	Z.	Mo	C	ਪ	Si	S	P	Μ'n	C	Analysis	Steelmaking Method	Heat
æ	CE																
									s (wt%)	Chemical Analysis (wt%)	Chemica						

Heat Test Type Microstructure Hardness Flattening Test Sm-1049 Heat Ferrite & Pearlite 77 Pass Longitudinal; 19.1mm x WT 44,100 69,500 0.63 41	BS			Γ
Microstructure Hardness Flattening Test Ferrite & Pearlite 77 Pass Longitudinal; 19.1mm x WT 44,100 69,500 0.63	BSM-1049	_		
Hardness Flattening Test Congitudinal; 19.1mm x WT 44,100 69,500 0.63	Heat	Test Type		
Flattening Test Congitudinal; 19.1mm x WT 44,100 69,500 0.63	Ferrite & Pearlite	Microstructure		
Tension Test Yield (Rt0.5) Tensile (Rm) Y/T Elongs	77	HRBW	Hardness	
n Test Yield (Rt0.5) Tensile (Rm) Y/T Elongs n GL psi psi (Rt0.5/Rm) 19.1mm x WT 44,100 69,500 0.63 ,	Pass	Flattening Test		Mechar
0.5) Tensile (Rm) Y/T Elongs psi (Rt0.5/Rm) 0 69,500 0.63	Longitudinal; 19.1mm x WT	50mm GL	Tension Test	lical Properties
\text{\text{m}} \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	44,100	psi	Yield (Rt0.5)	
(m) Elonga	69,500	psi	Tensile (Rm)	
Elongation (A) % 41	0.63	(Rt0.5/Rm)	Т/А	
	41	%	Elongation (A)	

<u></u>		
BSM-1049	Heat	
	Standard	Test
ţ	Sample Details	Impact Test
ı	eC	Temp
1	_	
ı	J	Impact
1	J	Energy
-	AVG	
ı	%	
	%	% Shear
	%	ear
1	AVG	
1	mm	
1	mm	Lateral Ex
	mm	pansion
ı	AVG	

Additional Details:

- results meet the corresponding requirements. Inc. in accordance with ASTM/ASME A/SA106-2011, A/SA53-2012, and the purchase order requirements, and that the ✓ This pipe product meets the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3 Sour We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing
- No weld repairs have been performed on this product.

Service, and NACE MR0103-2010 Section 2.1.

- This product has not come into contact with mercury during the Bri-Steel Manufacturing processes
- ✓ This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1.
- *Note that this product was hydrotested to 1000 psi for 5 seconds.
- **OD Tolerances as per API

Mill Test Certificate approved by:

Paul Sowden, T.T.

Assistant QA Manager