

Mill Test Certificate

2125-64 Avenue, Edmonton, AB Canada T6P 124 **Bri-Steel Manufacturing Inc.**

Tel: 001 (780) 469-6603

Fax: 001 (780) 469-6986

www.brichemsteel.com

NPS 16 XS Production Date: July 11, 2013

Production Method: **Hot Expansion** Product Heat Treatment: As-rolled

Product:

Seamless Carbon Steel Pipe

Product Heat Number:

BSM-1062

Product Size:

Product Standards: ASME B36.10-2004, ASTM/ASME A/SA106-2011 Grade B/C NDE, A/SA53-2012 Grade B Type S, NACE MR0175-2009, MR0103-2010

Product Markings: BRI-STEEL MFG ASTM/ASME A/SA106 GR B/C A/SA53 GR B NPS 16 XS 0.5 inchWT HEAT BSM-1062 (PIPE # LENGTH MASS) 82.771b/ft NDE SMLS NACE MR0175 2013/07 MADE IN CANADA.

77.7		1 000	1 033	1 033	1 033	1 033	220		04.11	7	,	0 10 70 0.0		1001
37 50	*	Dace	Dace	Dace	Pacc	Dace	, 000	À	82 77	DR.	7	NPS 16 XS 0 5 in WT	Heat	BSM-1062
Conditio		ASTM E309	ASTM E213 /	WT	OD	Insp.	Gauss	μR/hr	lb/ft	Length	Pieces	Product Size	Test Type	Heat
End	HydroTest	田	TU	TU		Visual	Res.Mag.	Geiger	Mass					
			Testing	Non-Destructive Testing	Non-I						S	Product Detail		

,	B			
1000	RSM-1062	Heat		
Vacuum Degas; Fully Killed	Blast Furnace; EAF; Ladle Refining;	Steelmaking Method		
Product	Heat	Analysis		
0.18	0.18	C		
0.90	0.91	Mn		
0.011	0.010	P		
0.006	0.003	S		Chemical
0.25	0.24	Si		Analysis (wt%
0.04	0.05	Ç		(wt%)
0.09	0.07	Cn		
0.01	0.01	Mo		
0.04	0.04	Z.		
0.003		<		
0.001	ı	= !		
0.001	1	Nb		
0.0001	0.0003	8		
0.35	r	(IIW)	Œ	
0.36		(CSA)	CE	

BSM-1062 Heat Ferrite & Pearlite 74	Heat Test Type Microstructure HRBW		
Pass	Flattening Test		Mecha
Longitudinal; 38.1mm x WT	50mm GL	Tension Test	Mechanical Properties
45,800	psi	Yield (Rt0.5)	
71,500	psi	Tensile (Rm)	
0.64	(Rt0.5/Rm)	Τ/Υ	
48	%	Elongation (A)	

	BS				
	M-1062	Heat			
	1	Standard	Test		
	1	Sample Details	Impact Test		
	1)e	Temp		
	,	ے			
	,	J	Impact		
	1	<u>_</u>	Energy		
	ı	AVG			
		%			
	3	%	% Shear		
		%	ear		
		AVG			
	ı	mm			
	ŧ.	mm	Lateral Ex		
CONTRACT CON		mm	pansion		
	1	AVG			

Additional Details:

results meet the corresponding requirements. Inc. in accordance with ASTM/ASME A/SA106-2011, A/SA53-2012, and the purchase order requirements, and that the We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing

Service, and NACE MR0103-2010 Section 2.1. √ This pipe product meets the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3 Sour

- No weld repairs have been performed on this product.
- This product has not come into contact with mercury during the Bri-Steel Manufacturing processes
- $\checkmark~$ This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1.
- *Note that this product was hydrotested to 1330 psi for 5 seconds.

Mill Test Certificate approved by:

いっつ

Paul Sowden, T.T.

Assistant QA Manager