

Mill Test Certificate

2125-64 Avenue, Edmonton, AB Canada T6P 1Z4 Bri-Steel Manufacturing Inc.

Tel: 001 (780) 469-6603

Fax: 001 (780) 469-6986 www.brichemsteel.com

NPS 20 STD Production Date: July 22, 2013

Production Method: **Hot Expansion** Product Heat Treatment: As-rolled

Product:

Seamless Carbon Steel Pipe

Product Heat Number:

BSM-1088

Product Size:

Product Standards: ASME B36.10-2004, API 5L-44th Ed. Grade B PSL1, ASTM/ASME A/SA106-2011 Grade B/C NDE, A/SA53-2012 Grade B Type S, NACE MR0175-2009, MR0103-2010

Product Markings: BRI-STEEL MFG <API> 5L-0898 API 5L GR B PSL1 ASTM/ASME A/SA106 GR B/C A/SA53 GR B NPS 20 STD 0.375 inchWT HEAT BSM-1088 (PIPE # LENGTH MASS) 78.6lb/ft NDE 900 PSI SMLS NACE MR0175 2013/07 MADE IN CANADA.

BSM-1088	Hea		
8	+	-	
Heat	Test Type		
NPS 20 STD 0.375 in.WT	Product Size		Product Detail
5	Pieces		5
DRL	Length		
78.60	lb/ft	Mass	
5	μR/hr	Geiger	
<20	Gauss	Res.Mag.	
Pass	Insp.	Visual	
Pass	OD		Non-D
Pass	WT	ST	Destructive 7
Pass	ASTM E213	UT	esting
Pass	ASTM E309	ET	
Pass	900 psi/5s	HydroTest	
32.5° Bevel	Condition	End	

Г	В	T		I
	BSM-1088	Heat		
Vacuum Degas; Fully Killed	Blast Furnace; EAF; Ladle Refining;	Steelmaking Method		
Product	Heat	Analysis		
0.22	0.22	C		
0.97	0.92	Mn		
0.011 0.009	0.010	٦		
0.009	0.009	S		Chemical
0.25	0.25	Si		Chemical Analysis (wt%)
0.04	0.04	੨		(wt%)
0.08	0.07	C		
0.01	0.01	Mo		
0.03	0.04	Z.		
0.004		<		
0.001	1	∄		
0.001	1	Nb		
0.0002	1	В		
0.40	-	(WII)	Œ	
0.41	1	(CSA)	CE	

_	_	-	7	_	-	_		_	_
	Heat			BSM-1088 Heat	1000	Heat			
	Standard	Test		Heat	1 Car 1 Abc	Test Type			
	Sample Details	Impact Test		Ferrite & Pearlite	ואווכוספוו מכנמו ב	Microstructure			
				76	MONE	LIDB\\\	Hardness		
	°C	Temp		Pass	riditiening rest				~
	_				Isai	1			1echar
	_	Impact Energy		Longitudinal; 38.1mm x WT	JUC	202	Tens		Mechanical Properties
	_	ergy		; 38.1r	Summ GL	2	Tension Test		Se
	AVG			nm x WT			st		
	%			47			Yield		
	%	% Shear		47,500	psi		Yield (Rt0.5)		
	%	ear		72			Tens		
-	AVG			72,000	psi		ensile (Rm)		
	m m			0	(Rto	1			
	mm	Lateral Expansion		0.66	(Kt0.5/Rm)	1	7		
	mm	xpansion		7			Elonga		
	AVG			12	%		Elongation (A)		

Additional Details:

BSM-1088

AVG

mm

mm

mm

AVG

and that the results meet the corresponding requirements. Inc. in accordance with API 5L-44th Ed., ASTM/ASME A/SA106-2011, A/SA53-2012, and the purchase order requirements, 🗸 We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing

Service, and NACE MR0103-2010 Section 2.1. ✓ This pipe product meets the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3 Sour

✓ No weld repairs have been performed on this product.

This product has not come into contact with mercury during the Bri-Steel Manufacturing processes

 $\checkmark~$ This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1.

Mill Test Certificate approved by:

Paul Sowden, T.T. 85 omder

Assistant QA Manager