

## Mill Test Certificate

2125-64 Avenue, Edmonton, AB Canada T6P 1Z4 Bri-Steel Manufacturing Inc.

Fax: 001 (780) 469-6986 Tel: 001 (780) 469-6603

www.brichemsteel.com

Product:

Seamless Carbon Steel Pipe Product Heat Number:

BSM-1136

Product Size:

NPS 18 TRUE80

Production Date:

August 7, 2013

Production Method: Hot Expansion Product Heat Treatment: As-rolled

Product Standards: ASME B36.10-2004, ASTM/ASME A/SA106-2011 Grade B NDE, A/SA53-2012 Grade B Type S, NACE MR0175-2009, MR0103-2010

Product Markings: BRI-STEEL MFG ASTM/ASME A/SA106 GR B A/SA53 GR B NPS 18 TRUE80 0.94 inchWT HEAT BSM-1136 (PIPE # LENGTH MASS) 170.81b/ft NDE SMLS NACE MR0175 2013/08 MADE IN CANADA.

	OCTT-IAICO	DCM 1136	חבמנ				
	неаг		rest Type	Tast Time			
	NPS 18 TRUE80 0.94 in.WT		Product Size				Product Detai
	w		Pieces				ls
	DRL		Length			Company of the Compan	
	170.80		lb/ft		SSPIAI		
	\$		µR/hr		Geiger	,	
	<20		Gauss		Kes.Mag.		
	Pass		nsp.	200 00000000000000000000000000000000000	Visual		
	Pass		9				Non-l
. 222	Pass		¥,	1	<u>_</u>		Non-Destructive Testin
. 433	Pass		ASTM F213	_			esting
1 033	Pass		ASTM F213 ASTM F300		7		
	*		300	- yara cac	HydroTect		
FIGHT EHO	Plain End		Condition	-	ת ס		

	BSM-1136		licar	L Dost	
vacuum Degas; Fully Killed	טומטנ רעווומנ	Diact Engage CAT. India national	Steeliligkilig Method	Ctoolmaking Mathed	
Product	Heat	Llos+	Analysis	•	
0.20	GT.0	010	<u></u>	)	
0.93	0.94	200	Μ'n		
0.014 0.003	/TO:0	224	70	ı	
0.003	0.003	3	S		Chemical Analysis (wt%)
0.32	0.31		S		Analysis
0.05	0.05		<del>ر</del>	2	(wt%)
0.06	0.05		Cu		
0.01	0.02		<u>S</u>		
0.03	0.03		Z		
0.003	0.004		<		
0.002	0.002	-	_!		
0.001	0.001	145	25		
1000.0	0.0004	c	D		
0.37	t	(AAII)	(IIIA/)	Ç	
0.38	č	(COA)	(CCA)	CE	

1	RS	Γ				Ę	DC	Γ	-	_	-	T	-		
SIAT TAIL	Heat BSM-1136		E 0.5+		SM-1136		70117C	ilear							
		Test Standard		Tect		BSM-1136 Heat		I cot I ype	Tort Time						
	sample Details		Impact Test Sample Details		Impact Test Sample Details			remite & Pearlite	Tamile Do Danie	Microstructure	A contract to the contract to				
								/6	1	HKBW		Hardness			
ī		j	remp	1		Pass		Flattening Test				≤			
,		_							Test						
		_	Impact Energy			Longitudinal: 38.1mm x WT		50mm GL		Tension Test		Mechanical Properties			
		AVG	_			8.1mm x WT		<u>و</u>		Test					
		%				49,400		DS.		Yield (Rt0.5)					
•	ò	%	% Shear	j						5					
	è	%	ear		00,00	68 500	Poor	DS:		Tensile (Rm)					
	3	200			6	รั			franch.	(Rm)					
		3			0.1	0.73	111000	(RtO 5/Rm)							
	111111	3	Lateral E		1	ٽ	lumi.	(Rm)		<b>⊣</b>		3			
20,60	111111		Lateral Expansion			_			Liongarion (A)	Flonga					
	AVG	210			ŏ	0	ò	ĸ	(4)	tion (A)					

## Additional Details:

results meet the corresponding requirements. Inc. in accordance with ASTM/ASME A/SA106-2011, A/SA53-2012, and the purchase order requirements, and that the We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing

Mill Test Certificate approved by:

Sombler

Service, and NACE MR0103-2010 Section 2.1. ✓ This pipe product meets the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3 Sour

No weld repairs have been performed on this product.

\*Note that this product was hydrotested to 1000 psi for 5 seconds. ✓ This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1.

This product has not come into contact with mercury during the Bri-Steel Manufacturing processes

Paul Sowden, T.T.

2013 AUG 15

Assistant QA Manager

cert # 164