

## Mill Test Certificate

Bri-Steel Manufacturing Inc. 2125-64 Avenue, Edmonton, AB Canada T6P 1Z4

Tel: 001 (780) 469-6603

Fax: 001 (780) 469-6986

www.brichemsteel.com

Product: Seamless Carbon Steel Pipe

Product Heat Number:

BSM-1269

Product Size: 16 XS

Production Date: Sep 23, 2013

Production Method: Hot Expansion

Product Heat Treatment:

As-rolled

Certificate No.: MTR- 000472

Product Standards:

Product Markings

ASME B36.10-2004, API 5L-45th Ed. Grade B PSL1, ASTM/ASME A/SA106-2011 Grade B/C NDE, A/SA53-2012 Grade B Type S, NACE MR0175-2009 MR0103-2010

| API> 5L-0898 API SPEC 5L NPS 16 XS 0.500 INCHWT GR B PSL1 SMLS 2013/09 NDE 1500PSI

| Product: Details    Pieces   Pieces   Length   Mass   Body   Mass   Mass |           |             | Heat Test Type Product Size Pieces Length N | Product: Details | маминаниямия HEAT BSM-1269 (PIPE # LENGTH M. |
|--|-----------|-------------|---|------------------|--|
| M/ASME A/SA106 GR B/C A/SA53 GR B NACE MR0175/MR0103 MADE IN CANADA  Non-Destructive Testing  No |           | μR/hr       | Geiger                                      |                  | lb/ft AST                                    |
| SA106 GR B/C A/SA53 GR B NACE MR0175/MR0103 MADE IN CANADA  Non-Destructive Testing  Visual OD UT UT ET HydroTest End Insp. WT ASTM E213 ASTM 1500 PSI/ 5 s Condition  | 1         | Gauss       | Res. Mag.                                   |                  | M/ASME A/S                                   |
| /C A/SA53 GR B NACE MR0175/MR0103 MADE IN CANADA  Non-Destructive Testing  OD UT UT ET HydroTest End WT ASTM E213 ASTM 1500 PSI/ 5 s Condition   | 7         | Insp.       | _   |                  | SA106 GR B,                                  |
| SR B NACE MR0175/MR0103 MADE IN CANADA  On-Destructive Testing  OT  OT  OT  OT  OT  OT  OT  ASTM E213. ASTM 1500 PSI/ 5 Condition  Description  Description  | Dacc      |             | 00  | Z                | /C A/SA53 G                                  |
| MR0175/MR0103 MADE IN CANADA  tive Testing  UT  ET  HydroTest  ASTM E213  ASTM 1500PSI/ 5 Condition  | Dace      | TW          | UT  | วท-Destruc       | R B NACE I                                   |
| 103 MADE IN CANADA  ET HydroTest End  ASTM 1500PSI/ 5 Condition  | Dace      | ASTM E213   | TU  | tive Testing     | MR0175/MR0                                   |
| HydroTest End 1500PSI/ 5 Condition   | Dace      | ASTM        | ET  |                  | )103 MADE                                    |
| End Condition  | Dace      | 1500 PSI/ 5 | HydroTest                                   |                  | IN CANADA                                    |
|  | Dlain End | S Condition | End   |                  |  |

|     |                  | BSM-1269   | Heat               |                         |
|-----|------------------|--|--------------------|-------------------------|
|     | Cegas, and Milea | Blast Furnace; EAF; Ladle Refining; Vacuum Degas: Fully Killed | Steelmaking Method |                         |
|     | Product          | Heat   | Test Type          |                         |
|     | 0.19             | 0.18   | С                  |                         |
|     | 0.91             | 0.91   | Mn                 |                         |
| 250 | 0.015            | 0.012  | Р                  |                         |
|     | 0.016            | 0.012  | S                  | Chemical Analysis (wt%) |
| -   | 0.26             | 0.23   | Si                 | Analysis (              |
|     | 0.07             | 0.03   | Cr                 | wt%)                    |
|     | 0.07             | 0.06   | Си                 |                         |
|     | 0.01             | 0.01   | Mo                 |                         |
|     | 0.04             | 0.04   | Z.                 |                         |
|     | 0.002            |  | ٧                  |                         |
|     | 100.0            |  | Ti                 |                         |
|     | 0.001            |  | dN                 |                         |
|     | 0.0001           | 0.0005   | В                  |                         |
|     | 0.37             | 1  | CE(IIW)            |                         |
|     | 0.37             | ı  | CE(CSA)            |                         |

|  | _                          | -          |                 | _                     |
|--|----------------------------|------------|-----------------|-----------------------|
|  | BSM-1269                   |            | Heat            |                       |
|  | Heat                       |            | Test Type       |                       |
|  | Ferrite & Pearlite         |            | Microstructure  |                       |
|  | 73 HRBW                    |            | Hardness        |                       |
|  | Pass                       |            | Flattening Test |                       |
|  | Longitudinal; 38.1 mm x WT | 50mm GL    | Tension Test    | Mechanical Properties |
| 20000  | 42,200                     | psi        | Yield (Rt0.5)   |                       |
|  | 71,000                     | psi        | Tensile (Rm)    |                       |
| The Commission of the commissi | 0.59                       | (Rt0.5/Rm) | 1/4             |                       |
|  | 44                         | %          | Elongation (A)  |                       |

| BSM-1269 |                | Heat           |  |
|----------|----------------|----------------|--|
|          | Standard       | Test           |  |
| 1        | Sample Details | Impact Test    |  |
|          | °C             | Temp           |  |
|          | _              |                |  |
| -        | _              | Impact         |  |
| 1        | J              | Energy         |  |
|          | AVG            | 200 20         |  |
| r        | %              |                |  |
| ,        | %              | % Shear        |  |
| 1        | %              | ıear           |  |
|          | AVG            |                |  |
| ı        | mm             |                |  |
| t        | mm             | Lateral Ex     |  |
|          | mm             | eral Expansion |  |
| t        | AVG            |                |  |

## Additional Details:

- ✓ We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing Inc. in accordance with API 5L-45th Ed., ASTM/ASME A/SA106-2011 Grade B/C A/SA53-2012, and the purchase order requirements, and that the results meet the corresponding requirements.
- √ This pipe product meets the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3 Sour Service-2009 NACE MR0103-2010 Section 2.1
- ✓ No weld repairs have been performed on this product.
- $\checkmark$  This product has not come into contact with mercury during the Bri-Steel Manufacturing processes
- $\checkmark$  This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1

Mill Test Certificate approved by:

Bounder 2013 SEP 30

Paul Sowden, T.T.

Assistant QA Manager