

## Mill Test Certificate

2125-64 Avenue, Edmonton, AB Canada T6P 1Z4 Bri-Steel Manufacturing Inc.

Tel: 001 (780) 469-6603

Fax: 001 (780) 469-6986 www.brichemsteel.com

Product: Seamless Carbon Steel Pipe Product Heat Number: BSM-1274 Product Size: 20 XS

Production Date:

Sep 25, 2013

As-rolled Certificate No.: MTR- 000487

ASME B36.10-2004, API 5L-45th Ed. Grade B PSL1, ASTM/ASME A/SA106-2011 Grade B/C NDE, A/SA53-2012 Grade B Type S, NACE MR0175-2009 MR0103-2010

**Product Markings** 

Product Standards:

Production Method:

Hot Expansion

Product Heat Treatment:

| API> 51-0898 API SPEC 5L NPS 20 XS 0.500 INCHWT GR B PSL1 SMLS 2013/09 NDE 1200PSI

| BSM-1274              |                         | Heat         |                         |
|-----------------------|-------------------------|--------------|-------------------------|
| Heat                  |                         | Test Type    |                         |
| NPS 20 XS 0.500in. WT |                         | Product Size | Product: Details        |
| 13                    |                         | Pieces       |                         |
| DRL                   |                         | Length       |                         |
| 104.1                 | lb/ft                   | Mass         |                         |
| <b>\$</b>             | μR/hr                   | Geiger       |                         |
| <10                   | Gauss                   | Res. Mag.    |                         |
| Pass                  | Insp.                   | Visual       |                         |
| Pass                  |                         | OD           | Z                       |
| Pass                  | WT                      | TU           | on-Destruc              |
| Pass                  | ASTM E213 ASTM          | UΤ           | Non-Destructive Testing |
| Pass                  | ASTM                    | ΕT           |                         |
| Pass                  | 1200 PSI/ 5 s Condition | HydroTest    |                         |
| 34° Bevel             | s Condition             | End          |                         |

|          |                    |  | STATE STREET, STATE OF THE STAT |      |      |                  | -                       |            | _            | 8    |      | -          | -     |         |       |                   |                 |           |
|----------|--------------------|--|--|------|------|------------------|-------------------------|------------|--------------|------|------|------------|-------|---------|-------|-------------------|-----------------|-----------|
| 1507 130 |                    | 100 00 100 0001                            |  |      |      |                  |                         |            |              |      | 0.00 |            |       | 1       |       |                   |                 |           |
| BSM-1274 | Heat               | NPS 20 XS 0.500in. WT                      |  | 13   | DRL  | 104.1            | \$                      | <10        |              | Pass | Pass | Pass       | Pass  |         | Pass  | Pass              | 3,              | 34° Bevel |
|          |                    |  |  |      |      |                  |                         |            |              |      |      |            |       |         |       |                   |                 |           |
|          |                    |  |  |      |      | 0                | Chemical Analysis (wt%) | nalysis (v | vt%)         |      |      |            |       |         |       |                   |                 |           |
| Heat     | Stee               | Steelmaking Method                         | Test Type  | С    | Mn   | P                | S                       | S:         | <del>ر</del> | C    | Mo   | <u>Z</u> . | <     | ⊐       | dN    | В                 | CE(IIW) CE(CSA) | CE(CSA)   |
| BSM-1274 | Blast Furnace; EAF | Blast Furnace; EAF; Ladle Refining; Vacuum | Heat   | 0.19 | 0.82 | 0.015 0.013 0.26 | 0.013                   |            | 0.06         | 0.01 |      | 0.04       |       |         |       |                   | 1               | 3         |
|          | orbus, i any in    |  | Product 0.22   | 0.22 | 0.89 | 0.020 0.013 0.24 | 0.013                   | 789        | 0.06         | 0.01 | 10.0 | 0.04       | 0.003 | 3 0.002 | 0.001 | 0.001 0.0002 0.39 | 0.39            | 0.39      |
|          |                    |  |  |      |      |                  |                         |            |              |      |      |            |       |         |       |                   |                 |           |

|   | BSM-1274                   |            | Heat            |                       |
|---|----------------------------|------------|-----------------|-----------------------|
|   | Heat                       |            | Test Type       |                       |
|   | Ferrite & Pearlite         |            | Microstructure  |                       |
|   | 74 HRBW                    |            | Hardness        | Marie Marie           |
|   | Pass                       |            | Flattening Test |                       |
|   | Longitudinal; 38.1 mm x WT | 50mm GL    | Tension Test    | Mechanical Properties |
|   | 43,900                     | psi        | Yield (Rt0.5)   |                       |
| 200 100 100 100 100 100 100 100 100 100 | 72,500                     | psi        | Tensile (Rm)    |                       |
|   | 0.61                       | (Rt0.5/Rm) | Υ/Τ             |                       |
|   | 43                         | %          | Elongation (A)  |                       |

| BSM-1274 - | Standard       | Heat        |
|------------|----------------|-------------|
| ı          | Sample Details | Impact Test |
| 1          | ငိ             | Temp        |
|            | _              |             |
|            | _              | Impact      |
| 1          | J              | Energy      |
| •          | AVG            |             |
| •          | %              |             |
| ı          | %              | % Shear     |
|            | %              | ear         |
|            | AVG            | 30d 30d     |
| ı          | mm             |             |
| r          | mm             | Lateral Ex  |
|            | mm             | Expansion   |
| i.         | AVG            |             |

Additional Details:

✓ We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing Inc. in accordance with API 5L-45th Ed., ASTM/ASME A/SA106-2011 Grade B/C A/SA53-2012, and the purchase order requirements, and that the results meet the corresponding requirements.

√ This pipe product meets the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3 Sour Service-2009 NACE MR0103-2010 Section 2.1

✓ No weld repairs have been performed on this product.

 $\checkmark$  This product has not come into contact with mercury during the Bri-Steel Manufacturing processes.

 $\checkmark$  This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1.

Mill Test Certificate approved by:

2013 OCT 01 Sanden

Paul Sowden, T.T.

Assistant QA Manager