

## Mill Test Certificate

Bri-Steel Manufacturing Inc. 2125-64 Avenue, Edmonton, AB Canada T6P 1Z4

Tel: 001 (780) 469-6603

Fax: 001 (780) 469-6986

www.brichemsteel.com

Product Size: 24 TRUE 80 Production Date: Nov 13, 2013

Certificate No.: MTR- 000698

Product Standards: ASME B36.10-2004, ASTM/ASME A/SA106-2011 Grade B NDE, A/SA53-2012 Grade B Type S, NACE MR0175-2009 MR0103-2010

Production Method:

Hot Expansion

Product:

Seamless Carbon Steel Pipe

Product Heat Number:

BSM-1406

Product Heat Treatment:

As-rolled

**Product Markings** BRI-STEEL NPS 24 TRUE 80 1.219 INCHWT SMLS 2013/11 NDE

MANUEZGEUERNIEUME HEAT BSM-1406 (PIPE # LENGTH MASS) 296.4lb/ft ASTM/ASME A/SA106 GR B A/SA53 GR B NACE MR0175/MR0103 MADE IN CANADA

| BSM-1406                   |                | неат         |                        |
|----------------------------|----------------|--------------|------------------------|
| Heat                       |                | lest lype    |                        |
| NPS 24 TRUE 80 1.219in. WT |                | Product Size | Product: Details       |
| 1                          |                | Pieces       |                        |
| DRL                        |                | Length       |                        |
| 296.4                      | lb/ft          | Mass         |                        |
| G                          | μR/hr          | Geiger       |                        |
| <10                        | Gauss          | Res. Mag.    |                        |
| Pass                       | Insp.          | Visual       |                        |
| Pass                       |                | 00           | z                      |
| Pass                       | WT             | Ţ            | Non-Destructive Testin |
| Pass                       | ASTM E213 ASTM | 5            | tive Testing           |
| Pass                       | ASTM           | ET           |                        |
| *                          |                | HydroTest    |                        |
| Plain End                  | Condition      | End          |                        |

|   | BSM-1406 |          |                    |                         |
|---|----------|----------|--------------------|-------------------------|
| Blast Furnace; EAF; Ladle Refining; Vacuum<br>Degas; Fully Killed |          | Distr.   | Steelmaking Method |                         |
| Product 0.21  | Heat     |          | Test Type          |                         |
|   | 0.19     |          | C                  |                         |
| 0.85  | 0.87     |          | Μ                  |                         |
| 0.011   | 0.008    |          | P                  |                         |
| 0.010   | 0.005    | Ī        | S                  | Chemical Analysis (wt%) |
| 0.23  | 0.22     | I        | <u>S</u>           | Analysis (              |
| 0.05  | 0.04     | l        | ე<br>ე             | (wt%)                   |
| 0.06  | 0.06     |          | 5                  |                         |
| 0.01  | 0.01     |          | <u>≼</u>           |                         |
| 0.05  | 0.04     |          | <u>z</u> .         |                         |
| 0.003   |          |          | <                  |                         |
| 0.001   |          |          | <b>T</b>           |                         |
| 0.001   |          |          | МЬ                 |                         |
| 0.0001  | 0.0003   |          | В                  |                         |
| 0.37  | ı        |          | CF(IIW)            |                         |
| 0.37  | 1        | 0=(00:1) | CF(CSA)            |                         |

|          |           |                    |          |                 | Mechanical Properties       |               |              |            |                |
|----------|-----------|--------------------|----------|-----------------|-----------------------------|---------------|--------------|------------|----------------|
| Heat     | Test Type | Microstructure     | Hardness | Flattening Test | Tension Test                | Yield (Rt0.5) | Tensile (Rm) | Υ/Τ        | Elongation (A) |
|          |           |                    |          |                 | 50mm GL                     | psi           | psi          | (Rt0.5/Rm) | %              |
| BSM-1406 | Heat      | Ferrite & Pearlite | 74 HRBW  | Pass            | Longitudinal; 19.05 mm x WT | 38,500        | 70,500       | 0.55       | 47             |
|          |           |                    |          |                 |                             |               |              |            |                |

|   | BSM-1406 |                | Heat              |
|---|----------|----------------|-------------------|
|   | 1        | Standard       | Test              |
|   | 1        | sample Details | Impact Test       |
| - | 1        | ٦,             | Temp              |
|   |          | _              |                   |
|   | ı        | ٦              | Impact            |
|   | ı        | _              | Energy            |
|   | 1        | AVG            |                   |
|   |          | %              |                   |
|   | ľ        | %              | % Shear           |
|   | 1        | %              | ear               |
|   | •        | AVG            |                   |
|   | ı        | mm             |                   |
| - | 1        | mm             | Lateral Expansion |
| - | 1        | mm             | pansion           |
|   | ,        | AVG            |                   |

## Additional Details:

- $\checkmark$  We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing Inc. in meet the corresponding requirements. accordance with ASTM/ASME A/SA106-2011 Grade B A/SA53-2012, and the purchase order requirements, and that the results
- √ This pipe product meets the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3 Sour Service-2009 NACE MR0103-2010 Section 2.1
- ✓ No weld repairs have been performed on this product.
- $\checkmark$  This product has not come into contact with mercury during the Bri-Steel Manufacturing processes.
- $\checkmark$  This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1.
- \* Note that this product was hydrotested to 1000 psi for 5 seconds.

Mill Test Certificate approved by:

Sanden 2019 JAN 04

Paul Sowden, T.T. Assistant QA Manager