

## Mill Test Certificate

2125-64 Avenue, Edmonton, AB Canada T6P 1Z4 Bri-Steel Manufacturing Inc.

Fax: 001 (780) 469-6986 Tel: 001 (780) 469-6603

www.brichemsteel.com

Seamless Carbon Steel Pipe

Product Heat Number:

BSM-1429 Product Size: 16 XS

Production Date:

Nov 21, 2013

Production Method: Hot Expansion

**Product Standards:** 

Product Heat Treatment:

As-rolled

ASME B36.10-2004, API 5L-45th Ed. Grade B PSL1, ASTM/ASME A/SA106-2011 Grade B/C NDE, A/SA53-2012 Grade B Type S, NACE MR0175-2009 MR0103-2010

Certificate No.: MTR- 000630

Heat Test Type		Product Markings
Test Type		kings
Product Size	Product: Details	API> 51-0898 API SPEC 5L NPS 16 XS 0.500 INCHWT GR B PSL1 SMLS 2013/11 NDE 1500PSI  MANNUARIUM HEAT BSM-1429 (PIPE # LENGTH MASS) 82.77lb/ft ASTM/ASME A/SA106 GR B/C A/SA53 GR B NACE MR0175/MR0103 MADE IN CANADA
Diococ		5L-0898 API SM-1429 (P
Dioces length Mass Goings Bos Mass Visual On III		SPEC 5L NPS
Marc		16 XS 0.500 H MASS) 82.
Coicor		INCHWT GF 77lb/ft ASTN
Doc Mag		R B PSL1 SM M/ASME A/S
Vicus		LS 2013/11 I A106 GR B/
3	No	NDE 1500PS C A/SA53 GI
-	Non-Destructive Testing	R B NACE M
-		R0175/MR0
		103 MADE II
FT IIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII		N CANADA

8	_				_	_		_
		BSM-1429				BSM-1429		Heat
25	Blast Furnace; EAF Degas; Fully Killed		Stee		Heat		lest Type	
The state of the s		Blast Furnace; EAF; Ladle Refining; Vacuum Degas: Fully Killed	Steelmaking Method			NPS 16 XS 0.500in. WT		Product Size
	Product 0.21	Heat	Test Type			VT		
	0.21	0.19	C			ω		Pieces
	0.95	0.94	N≥			DRL		Length
	0.95 0.017 0.005 0.26	0.010 0.004	P		200	82.77	lb/ft	Mass
	0.005	0.004	S	Chemical Analysis (wt%)		ŝ	μR/hr	Geiger
	_	0.25	Si	nalysis (v		^		
	0.03	0.03	Ç	vt%)		<10	Gauss	Res. Mag.
	0.09	0.07	Cu			Pass	Insp.	Visual
	0.02	0.01	Mo			Pass		8
	0.04	0.04	<u>Z</u>			Pass	TW	딕
-	0.003		<			Pass	ASTM	S
	0.001		Ti				ASTM E213 ASTM	
	0.001		Nb			Pass		E
	0.003   0.001   0.001   0.0003   0.38	0.0005	В			Pass	1500 PSI/ 5 s Condition	HydroTest
	0.38		CE(IIW)			_	5 s (	est
	0.38	1	CE(IIW) CE(CSA)			Plain End	Condition	End

BSM-1429		Heat	
Heat		Test Type	
Ferrite & Pearlite		Microstructure	
76 HRBW		Hardness	
Pass		Flattening Test	
Longitudinal; 38.1 mm x WT	50mm GL	Tension Test	Mechanical Properties
46,100	psi	Yield (Rt0.5)	
73,000	psi	Tensile (Rm)	
0.63	(Rt0.5/Rm)	Υ/Τ	
44	%	Elongation (A)	

	BSM-1429		Heat
	1	Standard	Test
	1	Sample Details	Impact Test
	ı	),	Temp
	1	_	
		J	Impact
	1	_	Energy
	•	AVG	
	1	%	
	1	%	% Shear
	,	%	ear
	<b>*</b>	AVG	
	1	mm	
	1	mm	Lateral Ex
-	1	mm	al Expansion
		AVG	

## Additional Details:

- $\checkmark$  We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing Inc. in and that the results meet the corresponding requirements. accordance with API 5L-45th Ed., ASTM/ASME A/SA106-2011 Grade B/C A/SA53-2012, and the purchase order requirements
- √ This pipe product meets the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3 Sour Service-2009 NACE MR0103-2010 Section 2.1
- ✓ No weld repairs have been performed on this product.
- $\checkmark$  This product has not come into contact with mercury during the Bri-Steel Manufacturing processes.
- $\checkmark$  This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1.

Mill Test Certificate approved by:

2013 NOV28

Paul Sowden, T.T.

Assistant QA Manager