

Mill Test Certificate

Bri-Steel Manufacturing Inc. 2125-64 Avenue, Edmonton, AB Canada T6P 1Z4

Tel: 001 (780) 469-6603

Fax: 001 (780) 469-6986 www.brichemsteel.com

Product: Seamless Carbon Steel Pipe Product Heat Number: BSM-1432

Production Method:

Hot Expansion

Product Heat Treatment:

Product Size: 14 XS

As-rolled

Certificate No.: MTR- 000643

Production Date:

Nov 21, 2013

Product Standards: ASME B36.10-2004, API 5L-45th Ed. Grade B PSL1, ASTM/ASME A/SA106-2011 Grade B/C NDE, A/SA53-2012 Grade B Type S, NACE MR0175-2009 MR0103-2010

Product Markings Heat Test Type | STEEL | <API> 5L-0898 API SPEC 5L NPS 14 XS 0.500 INCHWT GR B PSL1 SMLS 2013/11 NDE 1700PSI MITTER THE STREET HEAT BSM-1432 (PIPE # LENGTH MASS) 72.09lb/ft ASTM/ASME A/SA106 GR B/C A/SA53 GR B NACE MR0175/MR0103 MADE IN CANADA **Product Size** Product: Details Pieces Length Mass lb/ft Geiger μR/hr Res. Mag. Gauss Visual insp. 8 Non-Destructive Testing ¥ T ASTM E213 ASTM ET 1700 PSI/ HydroTest 5 5

BSM-1432

Heat

NPS 14 XS 0.500in. WT

14

DRL

72.09

ŝ

<10

Pass

Pass

Pass

Pass

Pass

Pass

32.5° Bevel Condition End

BSM-1432		Heat		
Blast Furnace; EAF; Ladle Refining; Vacuum Degas; Fully Killed		Steelmaking Method		
Product	Heat	Test Type		
0.22	0.19	С		
0.90	0.86	Mn		
0.90 0.010 0.005	0.010	Р		
0.005	0.005	S	Chemical Analysis (wt%)	
0.26	0.24	Si	Analysis (v	
0.04	0.04	Cr	wt%)	
0.08	0.06	Си		
0.01	0.01	Мо		
0.04	0.04	N:		
0.003		٧		
0.002		Ti		
0.001		Nb		
0.0003	0.0004	В		
0.38	1	CE(IIW)		
0.38	,	CE(CSA)		

	_			
	BSM-1432		Heat	
	Heat		Test Type	
	Ferrite & Pearlite		Microstructure	
	76 HRBW		Hardness	
	Pass		Flattening Test	
	Longitudinal; 38.1 mm x WT	50mm GL	Tension Test	Mechanical Properties
The state of the s	41,600	psi	Yield (Rt0.5)	
	71,000	psi	Tensile (Rm)	
	0.59	(Rt0.5/Rm)	Υ/Τ	
	46	%	Elongation (A)	

Additional Details:

- ✓ We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing Inc. in and that the results meet the corresponding requirements. accordance with API 5L-45th Ed., ASTM/ASME A/SA106-2011 Grade B/C A/SA53-2012, and the purchase order requirements,
- √ This pipe product meets the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3 Sour Service-2009 NACE MR0103-2010 Section 2.1
- ✓ No weld repairs have been performed on this product.
- \checkmark This product has not come into contact with mercury during the Bri-Steel Manufacturing processes
- \checkmark This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1.

Mill Test Certificate approved by:

20/3 DEC 03

Souder

Assistant QA Manager Paul Sowden, T.T.