

Mill Test Certificate

Bri-Steel Manufacturing Inc. 2125-64 Avenue, Edmonton, AB Canada T6P 1Z4

Tel: 001 (780) 469-6603

Fax: 001 (780) 469-6986 www.brichemsteel.com

Product: Seamless Carbon Steel Pipe

Product Heat Number:

BSM-1437

Product Size: 16 TRUE 80

Production Date:

Nov 25, 2013

Production Method: **Hot Expansion**

Product Heat Treatment:

As-rolled

Certificate No.: MTR- 000699

Product Standards: ASME B36.10-2004, API 5L-45th Ed. Grade B PSL1, ASTM/ASME A/SA106-2011 Grade B/C NDE, A/SA53-2012 Grade B Type S, NACE MR0175-2009 MR0103-2010

Product Markings | CAPI> 5L-0898 API SPEC 5L NPS 16 TRUE 80 0.844 INCHWT GR B PSL1 SMLS 2013/11 NDE 2500PSI AND SAME AS A SAME A SAME AS A SAME A SAME

Heat Test Type **Product Size** Product: Details Pieces Length Mass lb/ft Geiger μR/hr Res. Mag. Gauss Visual insp. 8 Non-Destructive Testing ¥ T ASTM E213 **ASTM** 円 2500 PSI/ HydroTest 5 5 Condition

BSM-1437

Heat

NPS 16 TRUE 80 0.844in. WT

10

DRL

136.5

읒

<10

Pass

Pass

Pass

Pass

Pass

Pass

Plain End

	BSM-1437	Heat		
		Steelmaking Method		
Product	Heat	Test Type		
0.22	0.19	0		
0.89	0.84	Ŋ,		
0.014	0.011	Ъ		
0.016 0.24	0.012	S	Chemical	
0.24	0.23	Si	Chemical Analysis (wt%)	
0.05	0.05	Cr	wt%)	
0.01	0.01	Cu		
0.00		Mo		
0.04	0.04	N;		
0.002		٧		
0.002		Ti		
0.001		Νb		
0.0003		В		
0.38	-	CE(IIW)		
0.38		CE(CSA)		

BSM-1437 Heat Ferrite & Pearlite 71 HRBW Pass Longitudinal; 38.1 mm x WT 41,100 70,000 0.59 43	Elongation (A) % 43	γ/T (Rt0.5/Rm) 0.59	Tensile (Rm) psi 70,000	Yield (Rt0.5) psi 41,100	Mechanical Properties Tension Test 50mm GL Longitudinal; 38.1 mm x WT	Test	Hardness 71 HRBW	Microstructure Ferrite & Pearlite	Test Type Heat	Heat BSM-1437
	%	(Rt0.5/Rm)	psi	psi	50mm GL					
GL psi psi (Rt	Elongation (A)	Υ/Τ	Tensile (Rm)	Yield (Rt0.5)	Tension Test	Flattening Test	Hardness	Microstructure	Test Type	Heat
Test Type Microstructure Hardness Flattening Test Tension Test Yield (Rt0.5) Tensile (Rm) 50mm GL psi psi (Rt					Mechanical Properties					

	BSM-1437		Heat
	I.	Standard	Test
	1	Sample Details	Impact Test
		°C	Temp
		_	
	1	٦	Impact
	ı	_	Energy
	1	AVG	
	ı	%	
	Ü	%	% Sh
	ı	%	Shear
	t	AVG	
	-	mm	
	1	mm	Lateral Ex
50 000	1	mm	Expansion
	ſ	AVG	

Additional Details:

- ✓ We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing Inc. in accordance with API 5L-45th Ed., ASTM/ASME A/SA106-2011 Grade B/C A/SA53-2012, and the purchase order requirements, and that the results meet the corresponding requirements.
- √ This pipe product meets the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3 Sour Service-2009 NACE MR0103-2010 Section 2.1
- ✓ No weld repairs have been performed on this product.
- \checkmark This product has not come into contact with mercury during the Bri-Steel Manufacturing processes
- \checkmark This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1.

Mill Test Certificate approved by:

Manager of Quality and R&D Kenton Dechant, P.Eng.