

Product:

Seamless Carbon Steel Pipe

Product Heat Number:

Mill Test Certificate

Bri-Steel Manufacturing Inc. 2125-64 Avenue, Edmonton, AB Canada T6P 1Z4 Tel: 001 (780) 469-6603 Fax: 001 (780) 469-6986

www.brichemsteel.com

BSM-1471 Product Size: 24 SCH 30 Production Date: Dec 12, 2013

Production Method: Hot Expansion **Product Heat Treatment:** As-rolled Certificate No.: MTR- 000677

Product Standards: ASME B36.10-2004, API 5L-45th Ed. Grade B PSL1, ASTM/ASME A/SA106-2011 Grade B/C NDE, A/SA53-2012 Grade B Type S, NACE MR0175-2009 MR0103-2010

Product Markings | STEEL | CAPI> 5L-0898 API SPEC 5L NPS 24 SCH 30 0.562 INCHWT GR B PSL1 SMLS 2013/12 NDE 1100PSI HEAT BSM-1471 (PIPE # LENGTH MASS) 140.8lb/ft ASTM/ASME A/SA106 GR B/C A/SA53 GR B NACE MR0175/MR0103 MADE IN CANADA

Heat						
Test Type	Product: Details	Product: Details				
Product Size						
Pieces						
Length						
Mass						
Geiger						
Res. Mag.						
Visual	Non-Destructive Testing	Non-Destructive Testing				
OD						
TU						
TU						
ΤЭ						
HydroTest						
End						

۲

ASTM E213

ASTM

1100 PSI/

Condition

BS	Г	Γ	1	BS
M-1471	Heat			BSM-1471
Blast Furnace; EAF, Degas; Fully Killed				Heat
EAF; Ladle Refining; Vacuum	elmaking Method			NPS 24 SCH 30 0.562in. WT
Heat	Test Type			ı. WT
0.18	С			2
0.85	Mn			DRL
0.009	Р			140.8
0.004	S	hemical /		<5
0.23	Si	\nalysis (v		<10
0.05	Cr	vt%)		10
0.06	Cu			Pass
0.02	Mo			Pass
0.03	Ni			Pass
	٧			Pass
	Ті			
	Nb			Pass
0.0004	В			Pass
1	CE(IIW)			
1	CE(CSA)			34° Bevel
	Ladle Reffining; Vacuum Heat 0.18 0.85 0.009 0.004 0.23 0.05 0.06 0.02 0.03	Test Type C Mn P S Si Cr Cu Mo Ni V Ti Nb B CE(IIW) Heat 0.18 0.85 0.009 0.004 0.23 0.05 0.06 0.02 0.03 - 0.0004 -	Test Type C Mn P S Si Cr Cu Mo Ni V Ti Nb B CE(IIW) Heat 0.18 0.85 0.009 0.004 0.23 0.05 0.06 0.02 0.03 0.004 0.0004 -	Chemical Analysis (wt%) Test Type C Mn P S Si Cr Cu Mo Ni V Ti Nb B CE(IIW) Heat 0.18 0.85 0.009 0.004 0.23 0.05 0.06 0.02 0.03 0.004 - 0.0004 -

	BSM-1471		Heat	
	Heat		Test Type	
	Ferrite & Pearlite		Microstructure	
	75 HRBW		Hardness	
	Pass		Flattening Test	
	Longitudinal; 38.1 mm x WT	50mm GL	Tension Test	Mechanical Properties
	46,500	psi	Yield (Rt0.5)	
A STATE OF THE PARTY OF THE PAR	71,000	psi	Tensile (Rm)	
	0.65	(Rt0.5/Rm)	Υ/Τ	
	44	%	Elongation (A)	

S8 S	ľ		
BSM-1471		Heat	
1	Standard	Test	
-	Sample Details	Impact Test	
ı	°C	Temp	
-	J		
	J	Impact	
-	J	Energy	
1	AVG		
1	%		
1	%	% Shear	
1	%	ear	
1	AVG		
U	mm		
ı	mm	Lateral Ex	
r	mm	pansion	
ı	AVG		

Additional Details:

- \checkmark We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing Inc. in and that the results meet the corresponding requirements. accordance with API 5L-45th Ed., ASTM/ASME A/SA106-2011 Grade B/C A/SA53-2012, and the purchase order requirements,
- \checkmark This pipe product meets the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3 Sour Service-2009 NACE MR0103-2010 Section 2.1
- ✓ No weld repairs have been performed on this product.
- ✓ This product has not come into contact with mercury during the Bri-Steel Manufacturing processes.
- \checkmark This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1.

Mill Test Certificate approved by:

2013 DEC 18

Paul Sowden, T.T. Assistant QA Manager