

Mill Test Certificate

2125-64 Avenue, Edmonton, AB Canada T6P 1Z4 Bri-Steel Manufacturing Inc.

Tel: 001 (780) 469-6603

Fax: 001 (780) 469-6986 www.brichemsteel.com

Seamless Carbon Steel Pipe Product Heat Number:

Product Standards: Production Method:

BSM-1473

Product Size: 20 SCH 60

Production Date: Dec 16, 2013

000680

Hot Expansion Product Heat Treatment: As-rolled Certificate No.: MTR-

Product Markings | CAPI > 51-0898 API SPEC 5L NPS 20 SCH 60 0.812 INCHWT GR B PSL1 SMLS 2013/12 NDE 1900PSI

THEAT BSM-1473 (PIPE # LENGTH MASS) 166.4lb/ft ASTM/ASME A/SA106 GR B A/SA53 GR B NACE MR0175/MR0103 MADE IN CANADA

ASME B36.10-2004, API 5L-45th Ed. Grade B PSL1, ASTM/ASME A/SA106-2011 Grade B NDE, A/SA53-2012 Grade B Type S, NACE MR0175-2009 MR0103-2010

BSM-1473		Heat Te	
Heat		Test Type	
NPS 20 SCH 60 0.812in. WT		Product Size	Product: Details
3		Pieces	
DRL		Length	
166.4	lb/ft	Mass	
<5	μR/hr	Geiger	
<10	Gauss	Res. Mag.	
Pass	Insp.	Visual	
Pass		OD	No
Pass	WT	TU	on-Destruc
Pass	ASTM E213 ASTM	UT	Non-Destructive Testing
Pass		ET	
Pass	1900 PSI/ 5 s Condition	HydroTest	
Plain End	Condition	End	

	BSM-1473	Heat			BSM-1473		ilear	
		Stee			Heat		iest Type	
		Steelmaking Method			NPS 20 SCH 60 0.812in. WT		FIDUACT SIZE	
Product	Heat	Test Type			WT			
0.20	0.19	С			З		Lieces religin	
0.84	0.87	Mn			DRL		rengui	
0.021 0.013	0.010	Р	0		166.4	lb/ft	IVIdos	
0.013	0.010	S	Chemical Analysis (wt%)	hemical Analysis (wt%)	<5	μR/hr	Geige	
0.25	0.24	Si				^		Geiger Nes. Mag.
0.11	0.05	Cr			vt%)	<10	Gauss	VIGE.
0.01	0.01	Cu				Pass	Insp.	VISUAI
0.00		Mo			Pass		0	
0.05	0.04	N:			Pass	WT		
0.002		٧			Pa	ASTM	_	
0.003		Ti				Pass	ASTM E213 ASTM	_
0.001		Nb				Pass		_
0.002 0.003 0.001 0.0003 0.37 0.37		В			Pass	1900 PSI/ 5 s Condition	nydrolest	
0.37		CE(IIW)				5 s	is a	
0.37	-	CE(IIW) CE(CSA)			Plain End	Condition	EUG	
17			-	. 60				

BSM-1473		Heat		
Heat		Test Type		
Ferrite & Pearlite		Microstructure		
76 HRBW		Hardness		
Pass		Flattening Test		
Longitudinal; 38.1 mm x WT	50mm GL	Tension Test	Mechanical Properties	
54,500	psi	Yield (Rt0.5)		
68,000	psi	Tensile (Rm)		
0.80	(Rt0.5/Rm)	Υ/Τ		
44	%	Elongation (A)		

	BSM-1473		Heat
	• (Standard	Test
The second secon	Ĭ	Sample Details	Impact Test
	•	°C	Temp
-		J	
	ı	J	Impact
	t	J	Energy
	1	AVG	
	1	%	
	1	%	% Shear
	1	%	ear
		AVG	
	1	mm	
	t	mm	Lateral Expansion
		mm	pansion
	ı	AVG	

Additional Details:

✓ We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing Inc. in accordance with API 5L-45th Ed., ASTM/ASME A/SA106-2011 Grade B A/SA53-2012, and the purchase order requirements, and that the results meet the corresponding requirements.

√ This pipe product meets the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3 Sour Service-2009 NACE MR0103-2010 Section 2.1

No weld repairs have been performed on this product.

 \checkmark This product has not come into contact with mercury during the Bri-Steel Manufacturing processes

 \checkmark This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1.

Mill Test Certificate approved by:

2013 DEC 20

Paul Sowden, T.T. Assistant QA Manager