

## Mill Test Certificate

2125-64 Avenue, Edmonton, AB Canada T6P 1Z4 Bri-Steel Manufacturing Inc.

Tel: 001 (780) 469-6603

Fax: 001 (780) 469-6986 www.brichemsteel.com

Product: Seamless Carbon Steel Pipe

Production Method:

**Product Markings** 

Product Heat Number:

Production Date: Jan 28, 2014

BSM-1577 Product Size: 20XS

Certificate No.: MTR- 000809

Product Standards: ASME B36.10-2004, API 5L-45th Ed. Grade B PSL1, ASTM/ASME A/SA106-2013 Grade B/C NDE, A/SA53-2012 Grade B Type S, NACE MR0175-2009 MR0103-2010 Hot Expansion Product Heat Treatment: As-rolled

| CAPI-STEEL | CAPI- 5L-0898 API SPEC 5L NPS 20 XS 0.500 INCHWT GR B PSL1 SMLS 2014/01 NDE 1200PSI

MOZAGIUMING HEAT BSM-1577 (PIPE # LENGTH MASS) 104.1lb/ft ASTM/ASME A/SA106 GR B/C A/SA53 GR B NACE MR0175/MR0103 MADE IN CANADA

	80.00	Product: Details							No	Non-Destructive	ive Testing			
Heat	Test Type	Product Size	Pieces	Length	Mass	Geiger	Res. Mag.	Visual	OD	TU	UΤ	ET	HydroTest	End
					lb/ft	μR/hr	Gauss	Insp.		TW	ASTM E213	ASTM	1200 PSI/ 5:	S Condition
BSM-1577	Heat	NPS 20 XS 0.500in. WT	2	DRL	104.1	<b>%</b>	<10	Pass	Pass	Pass	Pass	Pass	Pass	34° Bevel

		_		1		_
	BSM-1577	Heat			BSM-1577	
Degas, Fully Ni	Blast Furnace; EAF	Stee			Heat	
c	Blast Furnace; EAF; Ladle Refining; Vacuum	Steelmaking Method			NPS 20 XS 0.500in. WT	
Product 0.20	Heat	Test Type			\T	
0.20	0.19	С			2	
0.87	0.82	Mn			DRL	
0.87 0.016 0.015	0.015	Р	0		104.1	וט/ונ
0.015	0.013	S	Chemical Analysis (wt%)		<5	וויעון
0.28	0.26	Si	nalysis (v		<10	
0.07	0.06	Cr	vt%)		10	Gauss
0.01	0.01	Cu			Pass	msp.
0.00		Мо			Pass	
0.04	0.04	N:			Pass	00
0.003		٧			Pass	ASTIVI
0.005		II			ss	ASTIVI EZIS ASTIVI
0.001		Nb			Pass	
0.005   0.001   0.0003   0.37   0.37		В			Pass	TZUUPSI/ 5 S CUITAILIOIT
0.37	-	CE(IIW)				SC
0.37	ı	CE(IIW) CE(CSA)			34° Bevel	Collairion
			_	- 8		_

BSM-1577		Heat	
Heat		Test Type	
Ferrite & Pearlite		Microstructure	
75 HRBW		Hardness	
Pass		Flattening Test	
Longitudinal; 38.1 mm x WT	50mm GL	Tension Test	Mechanical Properties
42,700	psi	Yield (Rt0.5)	
72,500	psi	Tensile (Rm)	
0.59	(Rt0.5/Rm)	Υ/Τ	
42	%	Elongation (A)	

BSM-1577 -	Standard	Heat Test
•	Sample Details	Impact Test
	င	Temp
	J	
	J	Impact
ı	J	Energy
-	AVG	
t	%	
t	%	% Shear
t	%	ear
-	AVG	
	mm	
-	mm	Lateral E
-	mm	Expansion
	AVG	

## Additional Details:

- 🗸 We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing Inc. in and that the results meet the corresponding requirements. accordance with API 5L-45th Ed., ASTM/ASME A/SA106-2013 Grade B/C A/SA53-2012, and the purchase order requirements,
- $\checkmark$  This pipe product meets the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3 Sour Service-2009 NACE MR0103-2010 Section 2.1
- ✓ No weld repairs have been performed on this product.
- $\checkmark$  This product has not come into contact with mercury during the Bri-Steel Manufacturing processes
- √ This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1.

Mill Test Certificate approved by:

2014 JAN 30

Paul Sowden, T.T.

Assistant QA Manager