

Mill Test Certificate

Bri-Steel Manufacturing Inc. 2125-64 Avenue, Edmonton, AB Canada T6P 1Z4

Fax: 001 (780) 469-6986 www.brichemsteel.com Tel: 001 (780) 469-6603

Product: Seamless Carbon Steel Pipe

Product Heat Number:

BSM-1594 Product Size: 20S100

Production Date: Jan 31, 2014

Production Method: **Hot Expansion**

Product Standards:

Product Heat Treatment:

As-rolled

ASME B36.10-2004, ASTM/ASME A/SA106-2013 Grade B NDE, A/SA53-2012 Grade B Type S, NACE MR0175-2009 MR0103-2010

Certificate No.: MTR- 000832

Product Markings

BRI-STEEL] NPS 20 SCH 100 1.281 INCHWT SMLS 2014/01 NDE

MACE MACE BOWN-1594 (PIPE # LENGTH MASS) 256.1lb/ft ASTM/ASME A/SA106 GR B A/SA53 GR B NACE MR0175/MR0103 MADE IN CANADA

The state of the s										-				
Plain End	*	Pass	Pass	Pass	Pass	Pass	<10	<5	256.1	DRL	3	NPS 20 SCH 100 1.281in. WT	Heat	BSM-1594
COLIGICION		ASTIVI	WOLLAL LYTY	44.		msp.	Vauss	μιγιιι	וט/ונ					
Condition		ATM	ACTM E212 ACTM	S T		200	Carres	:.B/hr	15/4					
End	HydroTest	Е	U	<u></u>	OD	Visual	Res. Mag.	Geiger	Mass	Length	Pieces	Product Size	i est Type	неат
										-			T T	
			tive Testing	Non-Destructive Testing	Z							Product: Details		

0.39	0.39	0.0003	0.001	0.003	0.003	0.02	0.01	0.05	0.06	3 0.32	0.00	0.013	0.92	0.22	Product	Degas, rully Nilled	
9	ţ	0.0005	0.001	0.002	0.001	0.02	0.02	0.05	0.05	0.22	0.003	0.001	0.96	0.21	Heat	Blast Furnace; EAF; Ladle Refining; Vacuum	BSM-1594
CE(CSA)	CE(IIW)	В	Мb	Ті	٧	N:	Mo	Cu	Cr	Si	S	P	Mn	С	Test Type	Steelmaking Method	Heat
									wt%)	Analysis (Chemical Analysis (wt%)						

BSM			
-1594		Heat	
Heat		Test Type	
Ferrite & Pearlite		Microstructure	
75 HRBW		Hardness	
Pass		Flattening Test	
Longitudinal; 19.05 mm x WT	50mm GL	Tension Test	Viechanical Properties
38,000	psi	Yield (Rt0.5)	
69,500	psi	Tensile (Rm)	
0.55	(Rt0.5/Rm)	Υ/Τ	
50	%	Elongation (A)	
	Ferrite & Pearlite 75 HRBW Pass Longitudinal; 19.05 mm x WT 38,000 69,500	Heat Ferrite & Pearlite 75 HRBW Pass Longitudinal; 19.05 mm x WT 38,000 69,500 0.55	Test Type Microstructure Hardness Flattening Test Tension Test Yield (Rt0.5) Tensile (Rm) V/T E 50mm GL psi psi (Rt0.5/Rm) Heat Ferrite & Pearlite 75 HRBW Pass Longitudinal; 19.05 mm x WT 38,000 69,500 0.55

BSM-1594 -	Standard Sam	
1	sample Details	Impact Test
1	°C	Temp
ı	J	
-	J	Impact
ı	J	Energy
t	AVG	
Б	%	
L	%	% Shear
ı	%	ear
Ü	AVG	
Č	mm	
ı	mm	Lateral Ex
2	mm	xpansion
-	AVG	

Additional Details:

- ✓ We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing Inc. in meet the corresponding requirements. accordance with ASTM/ASME A/SA106-2013 Grade B A/SA53-2012, and the purchase order requirements, and that the results
- \checkmark This pipe product meets the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3 Sour Service-2009 NACE MR0103-2010 Section 2.1
- ✓ No weld repairs have been performed on this product.
- ✓ This product has not come into contact with mercury during the Bri-Steel Manufacturing processes.
- \checkmark This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1.
- * Note that this product was hydrotested to 1000 psi for 5 seconds.

Mill Test Certificate approved by:

16 Sandlen 2014 FEB 6

Assistant QA Manager Paul Sowden, T.T.