

Mill Test Certificate

2125-64 Avenue, Edmonton, AB Canada T6P 1Z4 Bri-Steel Manufacturing Inc.

Tel: 001 (780) 469-6603

Fax: 001 (780) 469-6986 www.bri-steel.com

Product: Seamless Carbon Steel Pipe

Product Heat Number: BSM-1608

Product Size: 20S100

Production Date: Feb 05, 2014

ASME B36.10-2004, ASTM/ASME A106-2014/SA106-2013 Grade B NDE, A53-2012/SA53-2013 Grade B Type S, NACE MR0175-2009 MR0103-2012 Hot Expansion Product Heat Treatment: As-rolled Certificate No.: MTR- 001530

Product Markings

Product Standards: Production Method:

NPS 20 SCH 100 1.281 INCHWT SMLS 2014/02 NDE

HEAT BSM-1608 (PIPE # LENGTH MASS) 256.1lb/ft ASTM/ASME A/SA106 GR B A/SA53 GR B NACE MR0175/MR0103 MADE IN CANADA

| | Name and Address of the Owner, when the Owner, which the Owner, | - | The same of the sa | Charles of the land of the lan | - Control of the Cont | | | | | | | | | |
|-----------|---|------|--|--|--|--------|-----------|--------|-------|--------|--------|----------------------------|-----------|----------|
| Plain End | * | Pass | Pass | Pass | Pass | Pass | <10 | <5 | 256.1 | DRL | 5 | NPS 20 SCH 100 1.281in. WT | Heat | BSM-1608 |
| Condition | | ASTM | ASTM E213 | TW | | Insp. | Gauss | μR/hr | lb/ft | | | | | |
| End | HydroTest | 旦 | UT | TU | OD | Visual | Res. Mag. | Geiger | Mass | Length | Pieces | Product Size | Test Type | Heat |
| | | | ive Testing | Non-Destructive Testing | NC | | | | | | | Product: Details | | |
| | | | | | | | | | | | | | | |

| BSIV | | | 1 | 8, | ı |
|-----------------------------|--|--|--|---|--|
| BSM-1608 | Heat | | | BSM-1608 | |
| Blast Furnace; | Stee | | | Heat | |
| EAF; Ladle Refining; Vacuum | | | | NPS 20 SCH 100 1.281ir | |
| Heat | Test Type | | | ı. WT | |
| 0.19 | С | | | 5 | |
| 0.87 | Mn | | | DRL | |
| 0.008 | Р | 0 | | 256.1 | |
| 0.003 | S | hemical A | | % | |
| 0.23 | Si | nalysis (v | | Λ | |
| 0.05 | Cr | vt%) | | | |
| 0.06 | Cu | | | Pass | |
| 0.01 | Мо | | | Pass | |
| 0.05 | N: | | | Pass | |
| | < | | | Pas | |
| | Ti | | | | |
| | Nb | | | Pass | |
| 0.0003 | В | | | * | |
| 1 | CE(IIW) | | | - | |
| 1 | CE(CSA) | | | lain End | |
| | Blast Furnace; EAF; Ladle Refining; Vacuum Heat 0.19 0.87 0.008 0.003 0.23 0.05 0.06 0.01 0.05 | Steelmaking Method Test Type C Mn P S Si Cr Cu Mo Ni V Ti Nb Blast Furnace; EAF; Ladle Refining; Vacuum Heat 0.19 0.87 0.008 0.003 0.23 0.05 0.01 0.05 0.05 0.01 0.05 0.05 0.00 | Steelmaking Method Test Type C Mn P S Si Cr Cu Mo Ni V Ti Nb B Blast Furnace; EAF; Ladle Refining; Vacuum Heat 0.19 0.87 0.008 0.003 0.23 0.05 0.06 0.01 0.05 0.05 0.003 | Chemical Analysis (wt%) Steelmaking Method Test Type C Mn P S Si Cr Cu Mo Ni V Ti Nb B Blast Furnace; EAF; Ladle Refining; Vacuum Heat 0.19 0.87 0.003 0.003 0.05 0.01 0.05 0.05 0.0003 | Heat NPS 20 SCH 100 1.281in. WT 5 DRL 256.1 <5 <10 Pass Pass< |

| | BSM-1608 | | Heat | |
|--|-----------------------------|------------|-----------------|-----------------------|
| | Heat | | Test Type | |
| | Ferrite & Pearlite | | Microstructure | |
| | 73 HRBW | | Hardness | |
| Transcation . | Pass | | Flattening Test | |
| The second secon | Longitudinal; 19.05 mm x WT | 50mm GL | Tension Test | Mechanical Properties |
| Control of the contro | 37,900 | psi | Yield (Rt0.5) | |
| | 65,500 | psi | Tensile (Rm) | |
| Section of the second section of the second section se | 0.58 | (Rt0.5/Rm) | ۲/۲ | |
| | 51 | % | Elongation (A) | |

| BSM-1608 | | Heat |
|----------|----------------|-------------------|
| t | Standard | Test |
| 1 | Sample Details | Impact Test |
| | °C | Temp |
| - | L | |
| - | J | Impact |
| • | J | Energy |
| | AVG | |
| u | % | |
| 1 | % | % Shea |
| E | % | ear |
| r | AVG | |
| | mm | ľ. |
| ı. | mm | Lateral Expansion |
| ï | mm | pansion |
| ï | AVG | |

Additional Details:

- ✓ We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing Inc. in accordance with corresponding requirements. Bri-Steel Manufacturing is registered and certified to ISO-9001:2008 and API Q1. ASTM/ASME A106-2014/SA106-2013 Grade B A53-2012/SA53-2013, and the purchase order requirements, and that the results meet the
- √ This pipe product meets the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3 Sour Service-2009 NACE MR0103-2012 Section 2.1
- ✓ No weld repairs have been performed on this product.
- \checkmark This product has not come into contact with mercury during the Bri-Steel Manufacturing processes.
- \checkmark This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1.
- * Note that this product was hydrotested to 1000 psi for 5 seconds.

Mill Test Certificate approved by:

Tonya Lam, C.E.T.

Assistant QA Manager