

Mill Test Certificate

2125-64 Avenue, Edmonton, AB Canada T6P 1Z4 Bri-Steel Manufacturing Inc. Tel: 001 (780) 469-6603

Fax: 001 (780) 469-6986

www.brichemsteel.com

Product: Seamless Carbon Steel Pipe

Product Heat Number:

BSM-1636 Product Size: 18XS

Production Date:

Feb 13, 2014

As-rolled

Certificate No.: MTR- 000875

Product Standards: Production Method: ASME B36.10-2004, API 5L-45th Ed. Grade B PSL1, ASTM/ASME A/SA106-2013 Grade B/C NDE, A/SA53-2012 Grade B Type S, NACE MR0175-2009 MR0103-2010 Hot Expansion Product Heat Treatment:

Product Markings | STEEL | <API> 5L-0898 API SPEC 5L NPS 18 XS 0.500 INCHWT GR B PSL1 SMLS 2014/02 NDE 1990PSI HEAT BSM-1636 (PIPE # LENGTH MASS) 93.45lb/ft ASTM/ASME A/SA106 GR B/C A/SA53 GR B NACE MR0175/MR0103 MADE IN CANADA

BSM-1636		Heat	
Heat		Test Type	6
NPS 18 XS 0.500in. WT		Product Size	Product: Details
ב		Pieces	
DRL		Length	
93.45	lb/ft	Mass	
<5	μR/hr	Geiger	
<10	Gauss	Res. Mag.	
Pass	Insp.	Visual	
Pass		00	Z
Pass	WT	TU	on-Destruc
Pass	ASTM E213 ASTM	T	Non-Destructive Testing
Pass		E	
Pass	1990 PSI/ 5 s Condition	HydroTest	
34° Bevel	Condition	End	

	BSM-1636	Heat	
Degas; Fully Killed	Blast Furnace; EAF; Ladle Refining; Vacuum	Steelmaking Method	
Product	Heat	Test Type	
0.21	0.20	С	
0.95	0.85	Mn	,
0.95 0.012 0.009	0.020 0.006 0.29	Р	
0.009	0.006	S	Chemical Analysis (wt%)
0.27	0.29	Si	Analysis (ı
0.04	0.07	Cr	wt%)
0.01	0.01	Си	
0.01		Мо	
0.04	0.04	Ni	
0.002		<	
0.003		□	
0.001		Nb	
0.0002		В	
0.39	-	CE(IIW)	
0.39	ι	CE(CSA)	

BSM-1636		Heat	
Heat		Test Type	
Ferrite & Pearlite		Microstructure	
74 HRBW		Hardness	
Pass		Flattening Test	
Longitudinal; 38.1 mm x WT	50mm GL	Tension Test	Mechanical Properties
41,900	psi	Yield (Rt0.5)	
71,500	psi	Tensile (Rm)	
0.59	(Rt0.5/Rm)	Υ/Τ	
43	%	Elongation (A)	
	Ferrite & Pearlite 74 HRBW Pass Longitudinal; 38.1 mm x WT 41,900 71,500	Heat Ferrite & Pearlite 74 HRBW Pass Longitudinal; 38.1 mm x WT 41,900 71,500	Test Type Microstructure Hardness Flattening Test Tension Test Yield (Rt0.5) Tensile (Rm) Heat Ferrite & Pearlite 74 HRBW Pass Longitudinal; 38.1 mm x WT 41,900 71,500

٢	В		_	
	BSM-1636		Heat	
	-	Standard	Test	
		Sample Details	Impact Test	
	L)	°C	Temp	
		J		
		ľ	Impact	
	1	J	Energy	
	i	AVG		
	t	%		
	E	%	% Shear	
		%	lear	
		AVG		
	ı	mm		
	,	mm	Lateral Ex	
	1	mm	pansion	
	ı	AVG		

Additional Details:

- ✓ We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing Inc. in and that the results meet the corresponding requirements. accordance with API 5L-45th Ed., ASTM/ASME A/SA106-2013 Grade B/C A/SA53-2012, and the purchase order requirements,
- \checkmark This pipe product meets the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3 Sour Service-2009 NACE MR0103-2010 Section 2.1
- No weld repairs have been performed on this product.
- \checkmark This product has not come into contact with mercury during the Bri-Steel Manufacturing processes
- \checkmark This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1.

Mill Test Certificate approved by:

ges ander 2014 FEB19

Assistant QA Manager Paul Sowden, T.T.