

Mill Test Certificate

Bri-Steel Manufacturing Inc. 2125-64 Avenue, Edmonton, AB Canada T6P 1Z4 Tel: 001 (780) 469-6603

Tel: 001 (780) 469-6603 Fax: 001 (780) 469-6986 www.brichemsteel.com

Product: Seamless Carbon Steel Pipe

Product Standards:

Product Heat Number:

BSM-1691 Prod

Product Size: 24STD

Production Date: Mar 10, 2014

Hot Expansion Product Heat Treatment:

As-rolled

Certificate No.: MTR- 000941

ASME B36.10-2004, API 5L-45th Ed. Grade B/X42 PSL1, ASTM/ASME A/SA106-2013 Grade B/C NDE, A/SA53-2012 Grade B Type S, NACE MR0175-2009 MR0103-2010

Product Markings | API & L/C No. > API SPEC 5L NPS 24 STD 0.375 INCHWT GR B/X42 PSL1 SMLS 2014/03 NDE 1180PSI

		MANUFACTURING INC. HEAT B	SM-1691 (F) JPE # LENG	TH MASS) 94.	.62lb/ft AST	M/ASME A/S	SA106 GR B/	/C A/SA53 G	R B NACE I	HEAT BSM-1691 (PIPE # LENGTH MASS) 94.62lb/ft ASTM/ASME A/SA106 GR B/C A/SA53 GR B NACE MR0175/MR0103 MADE IN CANADA	103 MADE	IN CANADA	
		Product: Details					The second secon		No	on-Destruc	Non-Destructive Testing			
Heat	Heat Test Type	Product Size	Pieces	Pieces Length	Mass	Geiger	Res. Mag.	Visual	OD	TU	UT	T3	_	HydroTest
					lb/ft	μR/hr	Gauss	Insp.		WT	ASTM E213 ASTM	ASTM	1	1180 PSI/ 5 s Condition
BSM-1691	Heat	NPS 24 STD 0.375in. WT	13	DRL	94.62	<5	<10	Pass	Pass	Pass	Pass	Pass	-	Pass

BSM-1691	Heat	NPS 24 STD 0.375in. WT		13	DRL	94.62	μR/hr <5	Gauss <10	Gauss <10	Insp. Pass	Pass	Pass	ASTM E213 ASTM Pass Pass	13 AS	1	1180 PSI/ S	1 - 6	5 s Condition 34° Bevel
						С	Chemical Analysis (wt%)	ıalysis (w	/t%)									
Heat	Ste	Steelmaking Method	Test Type	С	Mn	Р	S	Si	Cr	Cu	Мо	N:	٧	Ti	Nb		В	B CE(IIW) CE(CSA)
BSM-1691	Blast Furnace;	Blast Furnace; EAF; Ladle Refining; Vacuum	Heat	0.21	0.86	0.015 0.007	0.007	0.28	0.05	0.01		0.03						1
	Degas; rully nilled	ied	Product 0.25	0.25	0.88	0.025 0.010 0.31	0.010	_	0.06	0.01	0.00	0.03	0.005 0.	.003	0.001		0.0003	0.005 0.003 0.001 0.0003 0.41

	BSM-1691		Heat		
	Heat		Test Type		
	Ferrite & Pearlite		Microstructure		
	81 HRBW		Hardness		
	Pass		Flattening Test		
	Longitudinal; 38.1 mm x WT	50mm GL	Tension Test	Mechanical Properties	
The second secon	49,100	psi	Yield (Rt0.5)		
	78,500	psi	Tensile (Rm)		
	0.63	(Rt0.5/Rm)	У/Т		
	38	%	Elongation (A)		

Heat		Impact Test	Temp		Impact	Energy			% Shear	ear			Lateral Ex	Expansion	
Standard	rd	Sample Details	°C	J	J	_	AVG	%	%	%	AVG	mm	mm	mm	AVG
BSM-1691 -		L	-	L	t	ī	_	r	ı	-		-		ı	ā

Additional Details:

- 🗸 We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing Inc. in and that the results meet the corresponding requirements. accordance with API 5L-45th Ed., ASTM/ASME A/SA106-2013 Grade B/C A/SA53-2012, and the purchase order requirements,
- \checkmark This pipe product meets the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3 Sour Service-2009 NACE MR0103-2010 Section 2.1
- ✓ No weld repairs have been performed on this product.
- √ This product has not come into contact with mercury during the Bri-Steel Manufacturing processes.
- √ This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1.

Mill Test Certificate approved by:

produkter 2014 MAR/2

Paul Sowden, T.T. Assistant QA Manager