

Mill Test Certificate

Bri-Steel Manufacturing Inc. 2125-64 Avenue, Edmonton, AB Canada T6P 1Z4 Tel: 001 (780) 469-6603

Fax: 001 (780) 469-6986

www.bri-steel.com

Product: Seamless Carbon Steel Pipe Product Heat Number: BSM-1794 Product Size: 20S160 Production Date:

Apr 28, 2014

Production Method: Hot Expansion **Product Heat Treatment:** As-rolled Certificate No.: MTR- 001240

Product Standards: ASME B36.10-2004, ASTM/ASME A/SA106-2013 Grade B NDE, A/SA53-2012 Grade B Type S, NACE MR0175-2009 MR0103-2010

Product Markings | NBRI-STEEL | NPS 20 SCH 160 1.969 INCHWT SMLS 2014/04 NDE 2800PSI

HEAT BSM-1794 (PIPE # LENGTH MASS) 379Ib/ft ASTM/ASME A/SA106 GR B A/SA53 GR B NACE MR0175/MR0103 MADE IN CANADA

BSM-1794		Heat	
Heat		Test Type	
NPS 20 SCH 160 1.969in. WT		Product Size	Product: Details
1		Pieces	
DRL		Length	
379	lb/ft	Mass	
<5	μR/hr	Geiger	
<10	Gauss	Res. Mag.	
Pass	Insp.	Visual	
Pass		OD	No
Pass	WT	TU	on-Destruc
Pass	ASTM E213 ASTM	TU	Non-Destructive Testing
Pass	ASTM	ET	
Pass	2800 PSI/	HydroTest	
PI:	5 _S Cc		
Plain End	5 s Condition	End	

	_			BSN					
	Heat			BSM-1794	Heat				
	Test Type				Degas; Fully Nilled	Blast Furnace; EAF;	Steelm		
	Microstructure			Blast Furnace; EAF; Ladle Refining; Vacuum	Steelmaking Method				
	Har	38500 0000	Product 0.21	Heat	Test Type				
	Hardness		0.21	0.20	С				
	Flatten		0.92	0.94	Mn				
	Flattening Test		0.92 0.014 0.006 0.31 0.05	0.012	Ρ				
	Tension Test	Tension Test	Mechanic	0.006	0.002	S	Chemical Analysis (wt%)		
50			Tension Test	Tension Test	cal Proper Tens	0.31	0.30	Si	۸nalysis (۱
50mm GL					ion Test	ion Test	ties	0.05	0.03
			0.07	0.05	Си				
	Yiel		0.01	0.01	Mo				
psi	Yield (Rt0.5)		0.03	0.02	N:				
psi	Tensil		0.003	0.004	٧				
Si	Tensile (Rm)		0.002	0.003	Ti				
(Rt0.5/Rm	Υ/Τ		0.001	0.001	Nb				
_			0.0003 0.39		В				
%	Elongation (A)				CE(IIW) CE(CSA)				
	on (A)		0.39	r	CE(CSA)				

	_		2.00					
BSM-1794		Heat		BSM-1794	Heleson	Heat		
-	Test Standard			Heat		Test Type		
	rd	1 1		Ferrite & Pearlite		Microstructure		
r	Impact Test Sample Details							
				74 HRBW		Hardness		
+	°C	Temp		Pass		Flattening Test		
ı	J			רכ				
	J	Impact Energy		Longitudinal; 19.05 mm x WT	50	Ten		
	J	Energy		l; 19.05 m	50mm GL	Tension Test		
r	AVG			m x WT				
ï	%	% Shear				Yie		
1	%			42,700	psi	Yield (Rt0.5)		
1	%		ear		67,	-	Tensil	
	AVG			67,000	psi	Tensile (Rm)		
	mm	Lateral Expansion		0.64	(Rt0.5/Rm)	۲/۲		
•	mm		Lateral Expansion	Lateral E		5454340	(m)	
	mm				51	%	Elongation (A)	
	AVG					วท (A)		

Additional Details:

- 🗸 We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing Inc. in meet the corresponding requirements. accordance with ASTM/ASME A/SA106-2013 Grade B A/SA53-2012, and the purchase order requirements, and that the results
- \checkmark This pipe product meets the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3 Sour Service-2009 NACE MR0103-2010 Section 2.1
- ✓ No weld repairs have been performed on this product.
- √ This product has not come into contact with mercury during the Bri-Steel Manufacturing processes.
- \checkmark This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1.

Mill Test Certificate approved by:

Kenton Dechant, P.Eng.
Manager of Quality and R&D