

Mill Test Certificate

2125-64 Avenue, Edmonton, AB Canada T6P 1Z4 Bri-Steel Manufacturing Inc.

Tel: 001 (780) 469-6603

Fax: 001 (780) 469-6986

www.bri-steel.com

Product: Seamless Carbon Steel Pipe

Hot Expansion

Product Heat Number:

Product Heat Treatment:

As-rolled

BSM-1805 Product Size: 20S140

ASME B36.10-2004, ASTM/ASME A/SA106-2013 Grade B NDE, A/SA53-2012 Grade B Type S, NACE MR0175-2009 MR0103-2010

Production Date: Apr 30, 2014

Certificate No.: MTR- 001081

Product Markings

Product Standards: Production Method:

NPS 20 SCH 140 1.750 INCHWT SMLS 2014/04 NDE HEAT BSM-1805 (PIPE # LENGTH MASS) 341.11b/ft ASTM/ASME A/SA106 GR B A/SA53 GR B NACE MR0175/MR0103 MADE IN CANADA

BSM-1805		Heat	
Heat		Test Type	
NPS 20 SCH 140 1.750in. WT		Product Size	Product: Details
1		Pieces	
DRL		Pieces Length	
341.1	lb/ft	Mass	
<5	µR/hr	Geiger	
<10	Gauss	Res. Mag.	
Pass	Insp.	Visual	
Pass		OD	No
Pass	WT	TU	າກ-Destruct
Pass	ASTM E213 ASTM	TU	Non-Destructive Testing
Pass	ASTM	ET	
*		HydroTest	
Plain End	Condition	End	

		BSM-1805		Heat		
		Blast Furnace; EAF; Ladle Refining; Vacuum Degas: Fully Killed		Steelmaking Method		
	Product	Heat		Test Type		
	0.21	0.20		C		
	0.90	0.92		₹		
	0.012	0.010		ס		
20	0.007	0.003		s		Chemical Analysis (
	0.29	0.28		S:		Analysis (
	0.05	0.05		ڻ د	Superior Sup	s (wt%)
	0.08	0.08		5		
	0.01	0.01		<u></u>		
	0.03	0.03	200 000	<u>z</u> .		
	200.0	0.001		<		
	0.002	0.002	30000	T.		
	0.001	0.001		В		
	0.0004	0.0002		В		
	0.37	t		CE(IIW)		
	0.37	1		CE(CSA)		

				The state of the s					
50	0.62	000,39	41,100	Longitudinal; 19.05 mm x WT	Pass	75 HRBW	Ferrite & Pearlite	Heat	BSM-1805
%	(Rt0.5/Rm)	psi	psi	50mm GL					
Elongation (A)	Υ/Τ	Tensile (Rm)	Yield (Rt0.5)	Tension Test	Flattening Test	Hardness	Microstructure	Test Type	Heat
				Mechanical Properties					

Heat lest Impact Test Temp Impact Energy % Shear Lateral Expansion Standard Sample Details °C J J AVG % % AVG mm mm mm AVG BSM-1805																
Standard Sample Details °C J J AVG % % AVG mm mm	1	,	1	1	•	ា	sts	,	t	t		ı	Б	1		BSM-1805
Standard Sample Details °C J J AVG % % AVG mm mm																
lest Impact Test Temp Impact Energy % Shear Lateral Expa	AVG	mm	mm	mm	AVG	%	%	%	AVG	_	_	_	20	Sample Details	Standard	
		xpansion	Lateral E			near	% SI			Energy	Impact		Temp	Impact lest	lest	пеас

Additional Details:

- ✓ We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing Inc. in accordance with ASTM/ASME A/SA106-2013 Grade B A/SA53-2012, and the purchase order requirements, and that the results meet the corresponding requirements.
- √ This pipe product meets the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3 Sour Service-2009 NACE MR0103-2010 Section 2.1
- \checkmark No weld repairs have been performed on this product.
- \checkmark This product has not come into contact with mercury during the Bri-Steel Manufacturing processes.
- \checkmark This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1.
- * Note that this product was hydrotested to 1100 psi for 5 seconds.

Mill Test Certificate approved by:

2014 MAY 15 obsemblen

Assistant QA Manager Paul Sowden, T.T.

OD Tolerances as per API 5L