

Mill Test Certificate

Bri-Steel Manufacturing Inc. 2125-64 Avenue, Edmonton, AB Canada T6P 1Z4

Fax: 001 (780) 469-6986 Tel: 001 (780) 469-6603

www.bri-steel.com

Product: Seamless Carbon Steel Pipe

Production Method:

Hot Expansion

Product Heat Number: BSM-1812 Product Size: 20S140

Production Date: May 05, 2014

Product Heat Treatment: As-rolled

Certificate No.: MTR- 001075

Product Standards: ASME B36.10-2004, ASTM/ASME A/SA106-2013 Grade B NDE, A/SA53-2012 Grade B Type S, NACE MR0175-2009 MR0103-2010

Product Markings | BRI-STEEL | NPS 20 SCH 140 1.750 INCHWT SMLS 2014/05 NDE

ENTITION HEAT BSM-1812 (PIPE # LENGTH MASS) 341.11b/ft ASTM/ASME A/SA106 GR B A/SA53 GR B NACE MR0175/MR0103 MADE IN CANADA

BSM-1812 Heat		Heat Test Type	
NPS 20 SCH 140 1.750in. WT		ype Product Size	
.750in. WT			Product: Details
2		Pieces Length	
DRL		Length	
341.1	lb/ft	Mass	
<5	μR/hr	Geiger	
<10	Gauss	Geiger Res. Mag.	
Pass	Insp.	Visual	
Pass		OD**	Non
Pass	WT	TU	-Destruct
Pass	ASTM E213	TU	Non-Destructive Testing
Pass	STM E213 ASTM E309	ET	
•		HydroTest	
Plain End	Condition	End	

				-				The state of the s									
0.37	0.37	0.0004	0.001	0.002	0.003	0.02	0.01	0.07	0.05	0.30	0.012 0.006 0.30	0.012	0.90	0.21	Product	0	
,	,	0.0002	0.001	0.002	0.001	0.03	0.01	0.08	0.05	0.28	0.003	0.010	0.92	0.20	Heat	Blast Furnace, EAF, Ladle Refining, Vacuum Derast Fully Killed	BSM-1812
CE(CSA)	CE(IIW)	B	Nb	1	V	Z	Mo	5	Q	S	S	P	Mn	C	lest lype	Steelmaking Method	חבפנ
									(WE%)	Analysis	Chemical Analysis (wt%)				1	0	

BSM-1812 Heat Ferrite & Pearlite 76 HRBW Pass Longitudinal; 19.05 mm x WT 40,200 68,500	50mm GL psi psi	Heat Test Type Microstructure Hardness Flattening Test Tension Test Yield (Rt0.5) Tensile (Rn	Mechanical Properties
39 (psi psi	Yield (Rt0.5) Tensile (Rm)	
0.59 50	(Rt0.5/Rm) %	Y/T Elongation (/	

Heat	Test	Impact Test	Temp		Impact En	Energy			% Shea	ear		_	ateral b	pansion	
	Standard	Sample Details	ď	_	_	_	AVG	%	%	%	AVG	mm	mm	mm	AVG
BSM-1812	•	•	•		,	-	•	£		•	•	L	•	E	r

Additional Details:

✓ We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing Inc. in accordance with ASTM/ASME A/SA106-2013 Grade B A/SA53-2012, and the purchase order requirements, and that the results meet the corresponding requirements.

√ This pipe product meets the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3.

Sour Service-2009 NACE MR0103-2010 Section 2.1.

✓ No weld repairs have been performed on this product.

 \checkmark This product has not come into contact with mercury during the Bri-Steel Manufacturing processes

 \checkmark This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1

Note that this product was hydrotested to 1100 psi for 5 seconds.

**OD Tolerances as per API 5L

Mill Test Certificate approved by:

2014 MAY 15 16 Tunder

Paul Sowden, T.T. Assistant QA Manager